



EMS 347


HULL NO. 131

CORRECTION TABLE FOR TRIM AFT.			
FOR INNAGE GAUGES ONLY			
TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.
0'-6"	(+) 0' - 0 1/8"	(-) 0' - 0 1/8"	(+) 0' - 0 1/2"
1'-0"	(+) 0' - 0 1/4"	(-) 0' - 0 1/4"	(+) 0' - 1"
1'-6"	(+) 0' - 0 3/8"	(-) 0' - 0 3/8"	(+) 0' - 1 1/2"
2'-0"	(+) 0' - 0 1/2"	(-) 0' - 0 1/2"	(+) 0' - 2"
2'-6"	(+) 0' - 0 5/8"	(-) 0' - 0 5/8"	(+) 0' - 2 3/8"
3'-0"	(+) 0' - 0 3/4"	(-) 0' - 0 3/4"	(+) 0' - 2 7/8"
3'-6"	(+) 0' - 0 7/8"	(-) 0' - 0 3/4"	(+) 0' - 3 3/8"
4'-0"	(+) 0' - 1 1/8"	(-) 0' - 0 7/8"	(+) 0' - 3 7/8"
4'-6"	(+) 0' - 1 1/4"	(-) 0' - 1"	(+) 0' - 4 3/8"
5'-0"	(+) 0' - 1 3/8"	(-) 0' - 1 1/8"	(+) 0' - 4 7/8"

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED, TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 12/17/02 BY: 
INSPECTORATE AMERICA CORPORATION



EMS 347 OUTAGE TABLE

TANK NO. 1 PORT OR STAR

Table with columns: HULL NO 131, BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN, 0 FT., 1 FT., 2 FT., 3 FT., 4 FT., 5 FT., 6 FT., 7 FT., 8 FT., 9 FT., 10 FT., 11 FT., 12 FT., 13 FT., 14 FT. Each row corresponds to a specific gauge height and provides various measurements in feet.

REFERENCE GAUGE HEIGHT: 14.11" (TO RIM OF BALL VALVE LOCATED NEAR CENTER OF TANK)

* CAPACITY BELOW STRIKE POINT

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE

INSPECTORATE AMERICA CORPORATION logo

STRAPPED: 12/17/02

INSPECTORATE AMERICA CORPORATION

14.11" (TO RIM OF BALL VALVE LOCATED NEAR CENTER OF TANK)



EMS 347

OUTAGE TABLE

TANK NO. 3 PORT

HULL NO. 131

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

0 FT.		1 FT.		2 FT.		3 FT.		4 FT.		5 FT.		6 FT.		7 FT.		8 FT.		9 FT.		10 FT.		11 FT.		12 FT.		13 FT.		14 FT.							
W	D	W	D	W	D	W	D	W	D	W	D	W	D	W	D	W	D	W	D	W	D	W	D	W	D	W	D	W	D	W	D	W	D	W	D
0	14	0	14	0	14	0	14	0	14	0	14	0	14	0	14	0	14	0	14	0	14	0	14	0	14	0	14	0	14	0	14	0	14		
1	14	1	14	1	14	1	14	1	14	1	14	1	14	1	14	1	14	1	14	1	14	1	14	1	14	1	14	1	14	1	14	1	14		
2	14	2	14	2	14	2	14	2	14	2	14	2	14	2	14	2	14	2	14	2	14	2	14	2	14	2	14	2	14	2	14	2	14		
3	14	3	14	3	14	3	14	3	14	3	14	3	14	3	14	3	14	3	14	3	14	3	14	3	14	3	14	3	14	3	14	3	14		
4	14	4	14	4	14	4	14	4	14	4	14	4	14	4	14	4	14	4	14	4	14	4	14	4	14	4	14	4	14	4	14	4	14		
5	14	5	14	5	14	5	14	5	14	5	14	5	14	5	14	5	14	5	14	5	14	5	14	5	14	5	14	5	14	5	14	5	14		
6	14	6	14	6	14	6	14	6	14	6	14	6	14	6	14	6	14	6	14	6	14	6	14	6	14	6	14	6	14	6	14	6	14		
7	14	7	14	7	14	7	14	7	14	7	14	7	14	7	14	7	14	7	14	7	14	7	14	7	14	7	14	7	14	7	14	7	14		
8	14	8	14	8	14	8	14	8	14	8	14	8	14	8	14	8	14	8	14	8	14	8	14	8	14	8	14	8	14	8	14	8	14		
9	14	9	14	9	14	9	14	9	14	9	14	9	14	9	14	9	14	9	14	9	14	9	14	9	14	9	14	9	14	9	14	9	14		
10	14	10	14	10	14	10	14	10	14	10	14	10	14	10	14	10	14	10	14	10	14	10	14	10	14	10	14	10	14	10	14	10	14		
11	14	11	14	11	14	11	14	11	14	11	14	11	14	11	14	11	14	11	14	11	14	11	14	11	14	11	14	11	14	11	14	11	14		
12	14	12	14	12	14	12	14	12	14	12	14	12	14	12	14	12	14	12	14	12	14	12	14	12	14	12	14	12	14	12	14	12	14		
13	14	13	14	13	14	13	14	13	14	13	14	13	14	13	14	13	14	13	14	13	14	13	14	13	14	13	14	13	14	13	14	13	14		
14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14		

STRAPPED: 12/17/02

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE

INSPECTORATE AMERICA CORPORATION

REFERENCE GAUGE HEIGHT : 14'-10 3/4" (TO RIM OF BALL VALVE)
LOCATED NEAR CENTER OF TANK

* CAPACITY BELOW STRIKE POINT

