



BARGE "EMS-343"
ENTERPRISE MARINE SERVICE, LLC
OUTAGE TABLE

TANK NO. 1
PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 121

Table with columns: 0 FT., 1 FT., 2 FT., 3 FT., 4 FT., 5 FT., 6 FT., 7 FT., 8 FT., 9 FT., 10 FT., 11 FT., 12 FT., 13 FT., 14 FT. Each column contains multiple rows of numerical data representing measurements at different heights.

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 14'-1" (TO RIM OF 2" DIAMETER BALL VALVE)
LOCATED NEAR CENTER OF TANK

STRAPPED (180) PRESSURE-TIGHTENED TANKS TO REFLECT CHANGE
(SUPERSEDES ALL PREVIOUS DATED TABLES)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE
IN ACCORDANCE WITH APPLICABLE API STANDARDS AND
ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE

INSPECTORATE AMERICA CORPORATION



BARGE "EMS-343"
ENTERPRISE MARINE SERVICE, LLC
OUTAGE TABLE

HULL NO. 121

Table with columns: 0 FT., 1 FT., 2 FT., 3 FT., 4 FT., 5 FT., 6 FT., 7 FT., 8 FT., 9 FT., 10 FT., 11 FT., 12 FT., 13 FT., 14 FT. Each column contains multiple rows of numerical data representing measurements at different heights.

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 14'-11 1/4" (TO RIM OF 2" DIAMETER BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 11/001 REISSUED: 10/01/12
(SUPERSEDES ALL PREVIOUS DATED TABLES TO REFLECT CHANGE IN GAUGE HEIGHT) TANK NOT RESTRAINED.

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE

INSPECTORATE AMERICA CORPORATION

Signature of inspector



INSPECTORATE
ISO 9002 ACCREDITED

BARGE "EMS-343"
ENTERPRISE MARINE SERVICE, LLC
OUTAGE TABLE

TANK NO. 2
PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 121

IN	OUT	0 FT.	1 FT.	2 FT.	3 FT.	4 FT.	5 FT.	6 FT.	7 FT.	8 FT.	9 FT.	10 FT.	11 FT.	12 FT.	13 FT.	14 FT.
1	1	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
2	2	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
3	3	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
4	4	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
5	5	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
6	6	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
7	7	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
8	8	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
9	9	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
10	10	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
11	11	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
12	12	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
13	13	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
14	14	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
15	15	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
16	16	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
17	17	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
18	18	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
19	19	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
20	20	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
21	21	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
22	22	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
23	23	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
24	24	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
25	25	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
26	26	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
27	27	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
28	28	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
29	29	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
30	30	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
31	31	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
32	32	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
33	33	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752
34	34	5.2172	4.9937	4.7692	4.5447	4.3202	4.0957	3.8712	3.6467	3.4222	3.1977	2.9732	2.7487	2.5242	2.2997	2.0752

* CAPACITY BELOW STRIKE POINT
CAPACITIES GIVEN IN BARRELS OF 42 US GALLONS
REFERENCE GAUGE HEIGHT : 14'-11 1/4" (TO RIM OF 2" DIAMETER BALL VALVE)
LOCATED NEAR CENTER OF TANK)

STRAPPED: 11/8001 REISSUED: 10/6/12
(SUPERSEDES ALL PREVIOUS DATED TABLES TO REFLECT CHANGE IN GAUGE HEIGHT) TANK NOT RESTRAPPED.
WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE
INSPECTORATE AMERICA CORPORATION



INSPECTORATE ACCREDITED

BARGE "EMS-343"
ENTERPRISE MARINE SERVICE, LLC
 OUTAGE TABLE

BARGE SHOULD BE ON EVEN LEVEL KEEL WHEN GAUGES ARE TAKEN

CAPACITIES GIVEN IN BARRELS OF 42 US GALLONS		CAPACITY BELOW STRIKE POINT		REFERENCE GAUGE HEIGHT : 14"-11 1/4" (TO RIM OF 2" DIAMETER BALL VALVE LOCATED NEAR CENTER OF TANK)		HULL NO 121	
M	D	M	D	M	D	M	D
1	4,564.21	1	4,344.08	1	3,831.34	1	3,587.51
2	4,564.21	2	4,344.08	2	3,831.34	2	3,587.51
3	4,564.21	3	4,344.08	3	3,831.34	3	3,587.51
4	4,564.21	4	4,344.08	4	3,831.34	4	3,587.51
5	4,564.21	5	4,344.08	5	3,831.34	5	3,587.51
6	4,564.21	6	4,344.08	6	3,831.34	6	3,587.51
7	4,564.21	7	4,344.08	7	3,831.34	7	3,587.51
8	4,564.21	8	4,344.08	8	3,831.34	8	3,587.51
9	4,564.21	9	4,344.08	9	3,831.34	9	3,587.51
10	4,564.21	10	4,344.08	10	3,831.34	10	3,587.51
11	4,564.21	11	4,344.08	11	3,831.34	11	3,587.51
12	4,564.21	12	4,344.08	12	3,831.34	12	3,587.51
13	4,564.21	13	4,344.08	13	3,831.34	13	3,587.51
14	4,564.21	14	4,344.08	14	3,831.34	14	3,587.51
15	4,564.21	15	4,344.08	15	3,831.34	15	3,587.51
16	4,564.21	16	4,344.08	16	3,831.34	16	3,587.51
17	4,564.21	17	4,344.08	17	3,831.34	17	3,587.51
18	4,564.21	18	4,344.08	18	3,831.34	18	3,587.51
19	4,564.21	19	4,344.08	19	3,831.34	19	3,587.51
20	4,564.21	20	4,344.08	20	3,831.34	20	3,587.51
21	4,564.21	21	4,344.08	21	3,831.34	21	3,587.51
22	4,564.21	22	4,344.08	22	3,831.34	22	3,587.51
23	4,564.21	23	4,344.08	23	3,831.34	23	3,587.51
24	4,564.21	24	4,344.08	24	3,831.34	24	3,587.51
25	4,564.21	25	4,344.08	25	3,831.34	25	3,587.51
26	4,564.21	26	4,344.08	26	3,831.34	26	3,587.51
27	4,564.21	27	4,344.08	27	3,831.34	27	3,587.51
28	4,564.21	28	4,344.08	28	3,831.34	28	3,587.51
29	4,564.21	29	4,344.08	29	3,831.34	29	3,587.51
30	4,564.21	30	4,344.08	30	3,831.34	30	3,587.51
31	4,564.21	31	4,344.08	31	3,831.34	31	3,587.51
32	4,564.21	32	4,344.08	32	3,831.34	32	3,587.51
33	4,564.21	33	4,344.08	33	3,831.34	33	3,587.51
34	4,564.21	34	4,344.08	34	3,831.34	34	3,587.51
35	4,564.21	35	4,344.08	35	3,831.34	35	3,587.51
36	4,564.21	36	4,344.08	36	3,831.34	36	3,587.51
37	4,564.21	37	4,344.08	37	3,831.34	37	3,587.51
38	4,564.21	38	4,344.08	38	3,831.34	38	3,587.51
39	4,564.21	39	4,344.08	39	3,831.34	39	3,587.51
40	4,564.21	40	4,344.08	40	3,831.34	40	3,587.51
41	4,564.21	41	4,344.08	41	3,831.34	41	3,587.51
42	4,564.21	42	4,344.08	42	3,831.34	42	3,587.51
43	4,564.21	43	4,344.08	43	3,831.34	43	3,587.51
44	4,564.21	44	4,344.08	44	3,831.34	44	3,587.51
45	4,564.21	45	4,344.08	45	3,831.34	45	3,587.51
46	4,564.21	46	4,344.08	46	3,831.34	46	3,587.51
47	4,564.21	47	4,344.08	47	3,831.34	47	3,587.51
48	4,564.21	48	4,344.08	48	3,831.34	48	3,587.51
49	4,564.21	49	4,344.08	49	3,831.34	49	3,587.51
50	4,564.21	50	4,344.08	50	3,831.34	50	3,587.51
51	4,564.21	51	4,344.08	51	3,831.34	51	3,587.51
52	4,564.21	52	4,344.08	52	3,831.34	52	3,587.51
53	4,564.21	53	4,344.08	53	3,831.34	53	3,587.51
54	4,564.21	54	4,344.08	54	3,831.34	54	3,587.51
55	4,564.21	55	4,344.08	55	3,831.34	55	3,587.51
56	4,564.21	56	4,344.08	56	3,831.34	56	3,587.51
57	4,564.21	57	4,344.08	57	3,831.34	57	3,587.51
58	4,564.21	58	4,344.08	58	3,831.34	58	3,587.51
59	4,564.21	59	4,344.08	59	3,831.34	59	3,587.51
60	4,564.21	60	4,344.08	60	3,831.34	60	3,587.51
61	4,564.21	61	4,344.08	61	3,831.34	61	3,587.51
62	4,564.21	62	4,344.08	62	3,831.34	62	3,587.51
63	4,564.21	63	4,344.08	63	3,831.34	63	3,587.51
64	4,564.21	64	4,344.08	64	3,831.34	64	3,587.51
65	4,564.21	65	4,344.08	65	3,831.34	65	3,587.51
66	4,564.21	66	4,344.08	66	3,831.34	66	3,587.51
67	4,564.21	67	4,344.08	67	3,831.34	67	3,587.51
68	4,564.21	68	4,344.08	68	3,831.34	68	3,587.51
69	4,564.21	69	4,344.08	69	3,831.34	69	3,587.51
70	4,564.21	70	4,344.08	70	3,831.34	70	3,587.51
71	4,564.21	71	4,344.08	71	3,831.34	71	3,587.51
72	4,564.21	72	4,344.08	72	3,831.34	72	3,587.51
73	4,564.21	73	4,344.08	73	3,831.34	73	3,587.51
74	4,564.21	74	4,344.08	74	3,831.34	74	3,587.51
75	4,564.21	75	4,344.08	75	3,831.34	75	3,587.51
76	4,564.21	76	4,344.08	76	3,831.34	76	3,587.51
77	4,564.21	77	4,344.08	77	3,831.34	77	3,587.51
78	4,564.21	78	4,344.08	78	3,831.34	78	3,587.51
79	4,564.21	79	4,344.08	79	3,831.34	79	3,587.51
80	4,564.21	80	4,344.08	80	3,831.34	80	3,587.51
81	4,564.21	81	4,344.08	81	3,831.34	81	3,587.51
82	4,564.21	82	4,344.08	82	3,831.34	82	3,587.51
83	4,564.21	83	4,344.08	83	3,831.34	83	3,587.51
84	4,564.21	84	4,344.08	84	3,831.34	84	3,587.51
85	4,564.21	85	4,344.08	85	3,831.34	85	3,587.51
86	4,564.21	86	4,344.08	86	3,831.34	86	3,587.51
87	4,564.21	87	4,344.08	87	3,831.34	87	3,587.51
88	4,564.21	88	4,344.08	88	3,831.34	88	3,587.51
89	4,564.21	89	4,344.08	89	3,831.34	89	3,587.51
90	4,564.21	90	4,344.08	90	3,831.34	90	3,587.51
91	4,564.21	91	4,344.08	91	3,831.34	91	3,587.51
92	4,564.21	92	4,344.08	92	3,831.34	92	3,587.51
93	4,564.21	93	4,344.08	93	3,831.34	93	3,587.51
94	4,564.21	94	4,344.08	94	3,831.34	94	3,587.51
95	4,564.21	95	4,344.08	95	3,831.34	95	3,587.51
96	4,564.21	96	4,344.08	96	3,831.34	96	3,587.51
97	4,564.21	97	4,344.08	97	3,831.34	97	3,587.51
98	4,564.21	98	4,344.08	98	3,831.34	98	3,587.51
99	4,564.21	99	4,344.08	99	3,831.34	99	3,587.51
100	4,564.21	100	4,344.08	100	3,831.34	100	3,587.51

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION

STRAPPED: 11601 PREVIOUS DATED TABLES TO REFLECT CHANGE IN GAUGE HEIGHT TANK NOT RESTRAPPED.

TANK NO. 3
 PORT



ENTERPRISE MARINE SERVICE, LLC
OUTAGE TABLE

TANK NO. 3
STAR

CAPACITIES GIVEN IN BARRELS OR 42 US GALLONS		CAPACITY BELOW STRIKE POINT		REFERENCE GAUGE HEIGHT: 14"-10 3/4" (TO RIM OF 2" DIAMETER BALL VALVE)		LOCATED NEAR CENTER OF TANK		BARGE SHOULD BE ON EVEN LEVEL KEEL WHEN GAUGES ARE TAKEN												HULL NO. 121										
W	N	0 FT.	N	1 FT.	N	2 FT.	N	3 FT.	N	4 FT.	N	5 FT.	N	6 FT.	N	7 FT.	N	8 FT.	N	9 FT.	N	10 FT.	N	11 FT.	N	12 FT.	N	13 FT.	N	14 FT.
1/4	0		0	4,559.22	0	4,338.75	0	4,077.56	0	3,816.45	0	3,564.40	0	3,221.52	0	2,859.84	0	2,490.63	0	2,126.88	0	1,772.80	0	1,433.12	0	1,051.44	0	669.75	0	328.08
1/4	1/4	4,559.22	1/4	4,154.48	1/4	3,933.99	1/4	3,672.80	1/4	3,410.71	1/4	3,148.62	1/4	2,886.53	1/4	2,624.44	1/4	2,362.35	1/4	2,100.26	1/4	1,838.17	1/4	1,576.08	1/4	1,313.99	1/4	1,051.90	1/4	789.81
1/4	1/2	4,559.22	1/2	4,154.48	1/2	3,933.99	1/2	3,672.80	1/2	3,410.71	1/2	3,148.62	1/2	2,886.53	1/2	2,624.44	1/2	2,362.35	1/2	2,100.26	1/2	1,838.17	1/2	1,576.08	1/2	1,313.99	1/2	1,051.90	1/2	789.81
1/4	3/4	4,559.22	3/4	4,154.48	3/4	3,933.99	3/4	3,672.80	3/4	3,410.71	3/4	3,148.62	3/4	2,886.53	3/4	2,624.44	3/4	2,362.35	3/4	2,100.26	3/4	1,838.17	3/4	1,576.08	3/4	1,313.99	3/4	1,051.90	3/4	789.81
1/4	1	4,559.22	1	4,154.48	1	3,933.99	1	3,672.80	1	3,410.71	1	3,148.62	1	2,886.53	1	2,624.44	1	2,362.35	1	2,100.26	1	1,838.17	1	1,576.08	1	1,313.99	1	1,051.90	1	789.81
1/4	1 1/4	4,559.22	1 1/4	4,154.48	1 1/4	3,933.99	1 1/4	3,672.80	1 1/4	3,410.71	1 1/4	3,148.62	1 1/4	2,886.53	1 1/4	2,624.44	1 1/4	2,362.35	1 1/4	2,100.26	1 1/4	1,838.17	1 1/4	1,576.08	1 1/4	1,313.99	1 1/4	1,051.90	1 1/4	789.81
1/4	1 1/2	4,559.22	1 1/2	4,154.48	1 1/2	3,933.99	1 1/2	3,672.80	1 1/2	3,410.71	1 1/2	3,148.62	1 1/2	2,886.53	1 1/2	2,624.44	1 1/2	2,362.35	1 1/2	2,100.26	1 1/2	1,838.17	1 1/2	1,576.08	1 1/2	1,313.99	1 1/2	1,051.90	1 1/2	789.81
1/4	1 3/4	4,559.22	1 3/4	4,154.48	1 3/4	3,933.99	1 3/4	3,672.80	1 3/4	3,410.71	1 3/4	3,148.62	1 3/4	2,886.53	1 3/4	2,624.44	1 3/4	2,362.35	1 3/4	2,100.26	1 3/4	1,838.17	1 3/4	1,576.08	1 3/4	1,313.99	1 3/4	1,051.90	1 3/4	789.81
1/4	2	4,559.22	2	4,154.48	2	3,933.99	2	3,672.80	2	3,410.71	2	3,148.62	2	2,886.53	2	2,624.44	2	2,362.35	2	2,100.26	2	1,838.17	2	1,576.08	2	1,313.99	2	1,051.90	2	789.81
1/4	2 1/4	4,559.22	2 1/4	4,154.48	2 1/4	3,933.99	2 1/4	3,672.80	2 1/4	3,410.71	2 1/4	3,148.62	2 1/4	2,886.53	2 1/4	2,624.44	2 1/4	2,362.35	2 1/4	2,100.26	2 1/4	1,838.17	2 1/4	1,576.08	2 1/4	1,313.99	2 1/4	1,051.90	2 1/4	789.81
1/4	2 1/2	4,559.22	2 1/2	4,154.48	2 1/2	3,933.99	2 1/2	3,672.80	2 1/2	3,410.71	2 1/2	3,148.62	2 1/2	2,886.53	2 1/2	2,624.44	2 1/2	2,362.35	2 1/2	2,100.26	2 1/2	1,838.17	2 1/2	1,576.08	2 1/2	1,313.99	2 1/2	1,051.90	2 1/2	789.81
1/4	2 3/4	4,559.22	2 3/4	4,154.48	2 3/4	3,933.99	2 3/4	3,672.80	2 3/4	3,410.71	2 3/4	3,148.62	2 3/4	2,886.53	2 3/4	2,624.44	2 3/4	2,362.35	2 3/4	2,100.26	2 3/4	1,838.17	2 3/4	1,576.08	2 3/4	1,313.99	2 3/4	1,051.90	2 3/4	789.81
1/4	3	4,559.22	3	4,154.48	3	3,933.99	3	3,672.80	3	3,410.71	3	3,148.62	3	2,886.53	3	2,624.44	3	2,362.35	3	2,100.26	3	1,838.17	3	1,576.08	3	1,313.99	3	1,051.90	3	789.81
1/4	3 1/4	4,559.22	3 1/4	4,154.48	3 1/4	3,933.99	3 1/4	3,672.80	3 1/4	3,410.71	3 1/4	3,148.62	3 1/4	2,886.53	3 1/4	2,624.44	3 1/4	2,362.35	3 1/4	2,100.26	3 1/4	1,838.17	3 1/4	1,576.08	3 1/4	1,313.99	3 1/4	1,051.90	3 1/4	789.81
1/4	3 1/2	4,559.22	3 1/2	4,154.48	3 1/2	3,933.99	3 1/2	3,672.80	3 1/2	3,410.71	3 1/2	3,148.62	3 1/2	2,886.53	3 1/2	2,624.44	3 1/2	2,362.35	3 1/2	2,100.26	3 1/2	1,838.17	3 1/2	1,576.08	3 1/2	1,313.99	3 1/2	1,051.90	3 1/2	789.81
1/4	3 3/4	4,559.22	3 3/4	4,154.48	3 3/4	3,933.99	3 3/4	3,672.80	3 3/4	3,410.71	3 3/4	3,148.62	3 3/4	2,886.53	3 3/4	2,624.44	3 3/4	2,362.35	3 3/4	2,100.26	3 3/4	1,838.17	3 3/4	1,576.08	3 3/4	1,313.99	3 3/4	1,051.90	3 3/4	789.81
1/4	4	4,559.22	4	4,154.48	4	3,933.99	4	3,672.80	4	3,410.71	4	3,148.62	4	2,886.53	4	2,624.44	4	2,362.35	4	2,100.26	4	1,838.17	4	1,576.08	4	1,313.99	4	1,051.90	4	789.81
1/4	4 1/4	4,559.22	4 1/4	4,154.48	4 1/4	3,933.99	4 1/4	3,672.80	4 1/4	3,410.71	4 1/4	3,148.62	4 1/4	2,886.53	4 1/4	2,624.44	4 1/4	2,362.35	4 1/4	2,100.26	4 1/4	1,838.17	4 1/4	1,576.08	4 1/4	1,313.99	4 1/4	1,051.90	4 1/4	789.81
1/4	4 1/2	4,559.22	4 1/2	4,154.48	4 1/2	3,933.99	4 1/2	3,672.80	4 1/2	3,410.71	4 1/2	3,148.62	4 1/2	2,886.53	4 1/2	2,624.44	4 1/2	2,362.35	4 1/2	2,100.26	4 1/2	1,838.17	4 1/2	1,576.08	4 1/2	1,313.99	4 1/2	1,051.90	4 1/2	789.81
1/4	4 3/4	4,559.22	4 3/4	4,154.48	4 3/4	3,933.99	4 3/4	3,672.80	4 3/4	3,410.71	4 3/4	3,148.62	4 3/4	2,886.53	4 3/4	2,624.44	4 3/4	2,362.35	4 3/4	2,100.26	4 3/4	1,838.17	4 3/4	1,576.08	4 3/4	1,313.99	4 3/4	1,051.90	4 3/4	789.81
1/4	5	4,559.22	5	4,154.48	5	3,933.99	5	3,672.80	5	3,410.71	5	3,148.62	5	2,886.53	5	2,624.44	5	2,362.35	5	2,100.26	5	1,838.17	5	1,576.08	5	1,313.99	5	1,051.90	5	789.81

STRAPPED - 110601 (REVISED - 10/6/12)
 (SUPERSEDES ALL PREVIOUS DATED TABLES TO REFLECT CHANGE IN GAUGE HEIGHT) TANK NOT RESTRAINED.
 WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.
 INSPECTORATE AMERICA CORPORATION

* CAPACITY BELOW STRIKE POINT
 REFERENCE GAUGE HEIGHT: 14"-10 3/4" (TO RIM OF 2" DIAMETER BALL VALVE)
 LOCATED NEAR CENTER OF TANK



ENTERPRISE MARINE SERVICE, LLC
INNAVE TABLE

TANK NO. 1
PORT OR STAR

HULL NO. 121

Table with columns: N, O.F.T., 1.F.T., 2.F.T., 3.F.T., 4.F.T., 5.F.T., 6.F.T., 7.F.T., 8.F.T., 9.F.T., 10.F.T., 11.F.T., 12.F.T., 13.F.T., 14.F.T. and rows for various tank measurements.

CAPACITY BELOW STRIKE POINT
PORT REFERENCE GAUGE HEIGHT: 14'-1 1/4" (TO RIM OF 2" DIAMETER BALL VALVE LOCATED NEAR CENTER OF TANK)
STAR REFERENCE GAUGE HEIGHT: 14'-1 1/4" (TO RIM OF 2" DIAMETER BALL VALVE LOCATED NEAR CENTER OF TANK)

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN
CAPACITIES GIVEN IN BARRELS OF 42 US GALLONS
STRAPPED: 11/001 REISSUED: 10/6/12
(SUPERSIDES ALL PREVIOUS DATED TABLES TO REFLECT CHANGE IN GAUGE HEIGHT) TANK NOT STRAPPED.

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE
INSPECTORATE AMERICA CORPORATION



BARGE "EMS-343"
ENTERPRISE MARINE SERVICE, LLC
 INMAGE TABLE

TANK NO. 2
PORT OR STAR

HULL NO. 121

CAPACITY BELOW STRIKE POINT		REFERENCE GAUGE HEIGHT		CAPACITY ABOVE STRIKE POINT		REFERENCE GAUGE HEIGHT	
LOCATED NEAR CENTER OF TANK		14'-1 1/4" (TO RIM OF 2" DIAMETER BALL VALVE)		LOCATED NEAR CENTER OF TANK		14'-1 1/4" (TO RIM OF 2" DIAMETER BALL VALVE)	
M	N	M	N	M	N	M	N
0	182.22	0	394.65	0	773.02	0	1,161.39
1	22.48	1	392.74	1	771.11	1	1,159.48
2	28.73	2	400.83	2	769.20	2	1,157.57
3	30.99	3	408.92	3	767.29	3	1,155.66
4	38.95	4	417.01	4	765.38	4	1,153.75
5	42.91	5	425.11	5	763.47	5	1,151.84
6	48.88	6	433.20	6	761.56	6	1,149.93
7	54.84	7	441.29	7	759.65	7	1,148.02
8	62.29	8	449.38	8	757.74	8	1,146.11
9	67.74	9	457.47	9	755.83	9	1,144.20
10	77.19	10	465.56	10	753.92	10	1,142.29
11	88.28	11	473.65	11	752.01	11	1,140.38
12	93.37	12	481.74	12	750.10	12	1,138.47
13	101.47	13	489.83	13	748.19	13	1,136.56
14	109.56	14	497.92	14	746.28	14	1,134.65
15	117.65	15	506.02	15	744.37	15	1,132.74
16	125.74	16	514.11	16	742.46	16	1,130.83
17	133.83	17	522.20	17	740.55	17	1,128.92
18	141.92	18	530.29	18	738.64	18	1,127.01
19	150.01	19	538.38	19	736.73	19	1,125.10
20	158.10	20	546.47	20	734.82	20	1,123.19
21	166.19	21	554.56	21	732.91	21	1,121.28
22	174.28	22	562.65	22	731.00	22	1,119.37
23	182.38	23	570.74	23	729.09	23	1,117.46
24	190.47	24	578.83	24	727.18	24	1,115.55
25	198.56	25	586.93	25	725.27	25	1,113.64
26	206.65	26	595.02	26	723.36	26	1,111.73
27	214.74	27	603.11	27	721.45	27	1,109.82
28	222.83	28	611.20	28	719.54	28	1,107.91
29	230.92	29	619.29	29	717.63	29	1,106.00
30	239.01	30	627.38	30	715.72	30	1,104.09
31	247.10	31	635.47	31	713.81	31	1,102.18
32	255.19	32	643.56	32	711.90	32	1,100.27
33	263.28	33	651.65	33	710.00	33	1,098.36
34	271.38	34	659.74	34	708.09	34	1,096.45
35	279.47	35	667.84	35	706.18	35	1,094.54
36	287.56	36	675.93	36	704.27	36	1,092.63
37	295.65	37	684.02	37	702.36	37	1,090.72
38	303.74	38	692.11	38	700.45	38	1,088.81
39	311.83	39	700.20	39	698.54	39	1,086.90
40	319.92	40	708.29	40	696.63	40	1,085.00
41	328.01	41	716.38	41	694.72	41	1,083.09
42	336.10	42	724.47	42	692.81	42	1,081.18
43	344.20	43	732.56	43	690.90	43	1,079.27
44	352.29	44	740.65	44	689.00	44	1,077.36
45	360.38	45	748.74	45	687.09	45	1,075.45
46	368.47	46	756.84	46	685.18	46	1,073.54
47	376.56	47	764.93	47	683.27	47	1,071.63

* CAPACITY BELOW STRIKE POINT REFERENCE GAUGE HEIGHT 14'-1 1/4" (TO RIM OF 2" DIAMETER BALL VALVE) LOCATED NEAR CENTER OF TANK

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION

STRAPPED: 11/0/01 REISSUED: 10/16/12

(SUPERSEDES ALL PREVIOUS DATED TABLES TO REFLECT CHANGE IN GAUGE HEIGHT) TANK NOT RESTRAINED.



BARGE "EMS-343"
ENTERPRISE MARINE SERVICE, LLC
INNAGE TABLE

TANK NO. 3
PORT OR STAR

BARGE SHOULD BE ON EVEN KEEL WHEN GAUGES ARE TAKEN

HULL NO. 121

Table with 14 columns (N1-N14) and 14 rows (0-14) representing gauge readings in feet. Includes a section for CAPACITIES GIVEN IN BARRELS OF 42 US GALLONS and STRAPPED TANKS.

* CAPACITY BELOW STRIKE POINT

PORT REFERENCE GAUGE HEIGHT : 14'-11 1/4" (TO RIM OF 2" DIAMETER BALL VALVE LOCATED NEAR CENTER OF TANK)
STAR REFERENCE GAUGE HEIGHT : 14'-10 3/4" (TO RIM OF 2" DIAMETER BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE

INSPECTORATE AMERICA CORPORATION

Signature