



INSPECTORATE
ISO 9001: 2000

**BARGE "EMS-3001"
ENTERPRISE MARINE SERVICE
OUTAGE TABLE**

**TANK NO.
2 PORT**

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 325

M	N	0 FT.	1 FT.	2 FT.	3 FT.	4 FT.	5 FT.	6 FT.	7 FT.	8 FT.	9 FT.	10 FT.	11 FT.	12 FT.	13 FT.	14 FT.
0	0	5,139.64	0	4,797.35	0	4,426.84	0	4,066.33	0	3,665.81	0	3,315.30	0	2,944.79	0	2,574.28
1/4	1/4	5,136.66	1/4	4,799.63	1/4	4,419.12	1/4	4,048.51	1/4	3,678.10	1/4	3,307.58	1/4	2,937.07	1/4	2,566.56
1/2	1/2	5,132.18	1/2	4,791.91	1/2	4,411.40	1/2	3,970.38	1/2	3,299.86	1/2	2,929.35	1/2	2,929.35	1/2	2,558.84
3/4	3/4	5,127.71	3/4	4,774.19	3/4	4,403.68	3/4	3,662.66	3/4	3,292.15	3/4	2,921.63	3/4	2,921.63	3/4	2,551.12
1	1	5,123.23	1	4,766.48	1	4,395.96	1	4,025.45	1	3,654.94	1	3,284.63	1	2,913.87	1	2,543.40
1/4	1/4	5,118.76	1/4	4,758.76	1/4	4,388.24	1/4	4,017.73	1/4	3,647.22	1/4	3,276.71	1/4	2,906.20	1/4	2,535.68
1/2	1/2	5,113.00	1/2	4,751.04	1/2	4,380.53	1/2	4,010.01	1/2	3,639.50	1/2	3,268.99	1/2	2,898.48	1/2	2,527.96
3/4	3/4	5,107.24	3/4	4,743.32	3/4	4,372.81	3/4	4,002.29	3/4	3,631.78	3/4	3,259.27	3/4	2,890.76	3/4	2,520.25
2	2	5,101.47	2	4,735.60	2	4,365.09	2	3,994.57	2	3,624.06	2	3,253.55	2	2,883.04	2	2,512.53
1/4	1/4	5,095.71	1/4	4,727.88	1/4	4,357.37	1/4	3,986.86	1/4	3,616.34	1/4	3,245.83	1/4	2,875.32	1/4	2,504.81
1/2	1/2	5,088.56	1/2	4,720.16	1/2	4,349.65	1/2	3,979.14	1/2	3,608.62	1/2	3,238.11	1/2	2,867.60	1/2	2,497.09
3/4	3/4	5,081.51	3/4	4,712.44	3/4	4,341.93	3/4	3,971.42	3/4	3,600.91	3/4	3,230.39	3/4	2,859.88	3/4	2,489.37
3	3	5,074.57	3	4,704.72	3	4,334.21	3	3,963.70	3	3,593.19	3	3,222.67	3	2,852.16	3	2,481.65
1/4	1/4	5,067.52	1/4	4,697.00	1/4	4,326.49	1/4	3,955.98	1/4	3,585.47	1/4	3,214.96	1/4	2,844.44	1/4	2,473.93
1/2	1/2	5,059.80	1/2	4,689.29	1/2	4,318.77	1/2	3,948.26	1/2	3,577.75	1/2	3,207.24	1/2	2,836.72	1/2	2,466.21
3/4	3/4	5,052.08	3/4	4,681.57	3/4	4,311.05	3/4	3,940.54	3/4	3,570.03	3/4	3,199.52	3/4	2,829.01	3/4	2,458.49
4	4	5,044.36	4	4,673.85	4	4,303.34	4	3,932.82	4	3,562.31	4	3,191.80	4	2,821.29	4	2,450.77
1/4	1/4	5,036.64	1/4	4,666.13	1/4	4,295.62	1/4	3,925.10	1/4	3,554.59	1/4	3,184.08	1/4	2,813.57	1/4	2,443.06
1/2	1/2	5,028.92	1/2	4,658.41	1/2	4,287.90	1/2	3,917.38	1/2	3,546.87	1/2	3,176.36	1/2	2,805.85	1/2	2,435.34
3/4	3/4	5,021.20	3/4	4,650.69	3/4	4,280.18	3/4	3,909.67	3/4	3,539.15	3/4	3,168.64	3/4	2,798.13	3/4	2,427.62
5	5	5,013.48	5	4,642.97	5	4,272.46	5	3,901.95	5	3,531.43	5	3,160.92	5	2,790.41	5	2,419.90
1/4	1/4	5,005.76	1/4	4,635.25	1/4	4,264.74	1/4	3,894.23	1/4	3,523.72	1/4	3,153.20	1/4	2,782.69	1/4	2,412.18
1/2	1/2	4,998.05	1/2	4,627.53	1/2	4,257.02	1/2	3,886.51	1/2	3,516.00	1/2	3,145.48	1/2	2,774.97	1/2	2,404.46
3/4	3/4	4,990.33	3/4	4,619.81	3/4	4,249.30	3/4	3,878.79	3/4	3,508.28	3/4	3,137.77	3/4	2,767.25	3/4	2,396.74
6	6	4,982.61	6	4,612.10	6	4,241.58	6	3,871.07	6	3,500.56	6	3,130.05	6	2,759.53	6	2,389.02
1/4	1/4	4,974.89	1/4	4,604.38	1/4	4,233.86	1/4	3,863.35	1/4	3,492.84	1/4	3,122.33	1/4	2,751.82	1/4	2,381.30
1/2	1/2	4,967.17	1/2	4,596.66	1/2	4,226.15	1/2	3,855.63	1/2	3,485.12	1/2	3,114.61	1/2	2,744.10	1/2	2,373.58
3/4	3/4	4,959.45	3/4	4,588.94	3/4	4,218.43	3/4	3,847.91	3/4	3,477.40	3/4	3,106.89	3/4	2,736.38	3/4	2,365.87
7	7	4,951.73	7	4,581.22	7	4,210.71	7	3,840.19	7	3,469.68	7	3,099.17	7	2,728.66	7	2,358.15
1/4	1/4	4,944.01	1/4	4,573.50	1/4	4,202.99	1/4	3,832.48	1/4	3,461.96	1/4	3,091.45	1/4	2,720.94	1/4	2,350.43
1/2	1/2	4,936.29	1/2	4,565.78	1/2	4,195.27	1/2	3,824.76	1/2	3,454.24	1/2	3,083.73	1/2	2,713.22	1/2	2,342.71
3/4	3/4	4,928.57	3/4	4,558.06	3/4	4,187.55	3/4	3,817.04	3/4	3,446.53	3/4	3,076.01	3/4	2,705.50	3/4	2,334.99
8	8	4,920.86	8	4,550.34	8	4,179.83	8	3,809.32	8	3,438.81	8	3,068.29	8	2,697.78	8	2,327.27
1/4	1/4	4,913.14	1/4	4,542.62	1/4	4,172.11	1/4	3,801.60	1/4	3,431.09	1/4	3,060.58	1/4	2,690.06	1/4	2,319.55
1/2	1/2	4,905.42	1/2	4,534.91	1/2	4,164.39	1/2	3,793.88	1/2	3,423.37	1/2	3,052.86	1/2	2,682.34	1/2	2,311.83
3/4	3/4	4,897.70	3/4	4,527.19	3/4	4,156.67	3/4	3,786.16	3/4	3,415.65	3/4	3,045.14	3/4	2,674.63	3/4	2,304.11
9	9	4,889.98	9	4,519.47	9	4,148.96	9	3,778.44	9	3,407.93	9	3,037.42	9	2,666.91	9	2,296.39
1/4	1/4	4,882.26	1/4	4,511.75	1/4	4,141.24	1/4	3,770.72	1/4	3,400.21	1/4	3,029.70	1/4	2,659.19	1/4	2,288.68
1/2	1/2	4,874.54	1/2	4,504.03	1/2	4,133.52	1/2	3,763.00	1/2	3,392.49	1/2	3,021.98	1/2	2,651.47	1/2	2,280.96
3/4	3/4	4,866.82	3/4	4,496.31	3/4	4,125.80	3/4	3,755.29	3/4	3,384.77	3/4	3,014.26	3/4	2,643.75	3/4	2,273.24
10	10	4,859.10	10	4,488.59	10	4,118.08	10	3,747.57	10	3,377.05	10	3,006.54	10	2,636.03	10	2,265.52
1/4	1/4	4,851.38	1/4	4,480.87	1/4	4,110.36	1/4	3,739.85	1/4	3,369.34	1/4	2,998.82	1/4	2,628.31	1/4	2,257.80
1/2	1/2	4,843.67	1/2	4,473.15	1/2	4,102.64	1/2	3,732.13	1/2	3,361.62	1/2	2,991.10	1/2	2,620.59	1/2	2,250.08
3/4	3/4	4,835.95	3/4	4,465.43	3/4	4,094.92	3/4	3,724.41	3/4	3,353.90	3/4	2,983.39	3/4	2,612.87	3/4	2,242.36
11	11	4,828.23	11	4,457.72	11	4,087.20	11	3,716.69	11	3,346.18	11	2,975.67	11	2,605.15	11	2,234.64
1/4	1/4	4,820.51	1/4	4,450.00	1/4	4,079.48	1/4	3,708.97	1/4	3,338.46	1/4	2,967.95	1/4	2,600.44	1/4	2,226.92
1/2	1/2	4,812.79	1/2	4,442.28	1/2	4,071.76	1/2	3,701.25	1/2	3,330.74	1/2	2,960.23	1/2	2,592.72	1/2	2,219.20
3/4	3/4	4,805.07	3/4	4,434.56	3/4	4,064.05	3/4	3,693.53	3/4	3,323.02	3/4	2,952.51	3/4	2,584.50	3/4	2,211.49

CAPACITIES GIVEN IN BARRELS OF 42 US GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 14'-1" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

[Signature]
INSPECTORATE AMERICA CORPORATION

STRAPPED: 312795



INSPECTORATE ISO 9001: 2000

BARGE "EMS-3001" ENTERPRISE MARINE SERVICE OUTAGE TABLE

TANK NO. 2 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 325

Table with 14 columns: M, 0 FT., M, 1 FT., M, 2 FT., M, 3 FT., M, 4 FT., M, 5 FT., M, 6 FT., M, 7 FT., M, 8 FT., M, 9 FT., M, 10 FT., M, 11 FT., M, 12 FT., M, 13 FT., M, 14 FT.

* CAPACITY BELOW STRIKE POINT REFERENCE GAUGE HEIGHT : 14'-10 3/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK) WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION

