



BARGE "EMS 355"
Enterprise Marine Services LLC

HULL NO. 4479

CORRECTION TABLE FOR TRIM AFT.

FOR INNAGE GAUGES ONLY

TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.
0'-6"	(-) 0' - 0 1/8"	(-) 0' - 0 1/8"	(-) 0' - 0 1/8"
1'-0"	(-) 0' - 0 3/8"	(-) 0' - 0 1/4"	(-) 0' - 0 3/8"
1'-6"	(-) 0' - 0 1/2"	(-) 0' - 0 3/8"	(-) 0' - 0 1/2"
2'-0"	(-) 0' - 0 5/8"	(-) 0' - 0 1/2"	(-) 0' - 0 5/8"
2'-6"	(-) 0' - 0 3/4"	(-) 0' - 0 3/4"	(-) 0' - 0 7/8"
3'-0"	(-) 0' - 1"	(-) 0' - 0 7/8"	(-) 0' - 1"
3'-6"	(-) 0' - 1 1/8"	(-) 0' - 1"	(-) 0' - 1 1/4"
4'-0"	(-) 0' - 1 1/4"	(-) 0' - 1 1/8"	(-) 0' - 1 3/8"
4'-6"	(-) 0' - 1 1/2"	(-) 0' - 1 1/4"	(-) 0' - 1 1/2"
5'-0"	(-) 0' - 1 5/8"	(-) 0' - 1 3/8"	(-) 0' - 1 3/4"

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED,
TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 12/10/04

BY:


INSPECTORATE AMERICA CORPORATION

BARGE "EMS 355"
Enterprise Marine Services LLC



INNAGE TABLE

TANK NO. 1
PORT OR STAR

HULL NO. 4479

Table with columns for measurement points (0 FT. to 14 FT.) and rows for various tank sections. Includes header 'BARGE SHOULD BE ON EVEN LEVEL KEEL WHEN GAUGES ARE TAKEN' and 'CAPACITIES GIVEN IN BARRELS OR 42 US GALLONS'.

PORT REFERENCE GAUGE HEIGHT: 15'-3" RIM OF 2" DIAMETER BALL VALVE
LOCATED NEAR CENTER OF TANK

STAR REFERENCE GAUGE HEIGHT: 15'-3 1/4" RIM OF 2" DIAMETER BALL VALVE
LOCATED NEAR CENTER OF TANK

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION

BARGE "EMS 355"
Enterprise Marine Services LLC

INNAGE TABLE



TANK NO. 2
PORT OR STAR

HULL NO. 4479

Table with columns for Gauge No., Gauge Name, and various numerical readings (0 FT. to 14 FT.). Includes a note: 'BARGE SHOULD BE ON EVEN LEVEL KEEL WHEN GAUGES ARE TAKEN'.

* CAPACITY BELOW STRIKE POINT

PORT REFERENCE GAUGE HEIGHT : 15'-2 3/4" (RIM OF 2" DIAMETER BALL VALVE LOCATED NEAR CENTER OF TANK)
STAR REFERENCE GAUGE HEIGHT : 15'-3" (RIM OF 2" DIAMETER BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION
[Signature]

