



BARGE "EMS-328"
ENTERPRISE MARINE SERVICES LLC
INNAUGE TABLE

1 PORT OR STAR

Table with columns: O. FT., 1 FT., 2 FT., 3 FT., 4 FT., 5 FT., 6 FT., 7 FT., 8 FT., 9 FT., 10 FT., 11 FT., 12 FT., 13 FT., 14 FT. Rows contain numerical data for each port/star measurement.

* CAPACITIES BELOW STRIKE POINT.

PORT REFERENCE GAUGE HEIGHT: 15'-0" (TO RIM OF 2" DIAMETER BALL VALVE)
LOCATED NEAR CENTER OF TANK

STAR REFERENCE GAUGE HEIGHT: 14'-1 1/2" (TO RIM OF 2" DIAMETER BALL VALVE)
LOCATED NEAR CENTER OF TANK

PORT REFERENCE GAUGE HEIGHT: 15'-0" (TO RIM OF 2" DIAMETER BALL VALVE)
LOCATED NEAR CENTER OF TANK

STAR REFERENCE GAUGE HEIGHT: 14'-1 1/2" (TO RIM OF 2" DIAMETER BALL VALVE)
LOCATED NEAR CENTER OF TANK

INSPECTORATE AMERICA CORPORATION

STRAPPED: 7/09/12 (SUSPENSES ALL PREVIOUS DATED TABLES TO REFLECT CHANGE IN GAUGE HEIGHT.)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.



BARGE "EMS-328"
ENTERPRISE MARINE SERVICES LLC
INMAGE TABLE

2 PORT OR STAR

HULL NO. 338

Table with columns: M, O, F, T, N, 1 FT., 2 FT., 3 FT., 4 FT., 5 FT., 6 FT., 7 FT., 8 FT., 9 FT., 10 FT., 11 FT., 12 FT., 13 FT., 14 FT. Rows contain numerical data for each measurement point.

* CAPACITY BELOW STRIKE POINT.

PORT REFERENCE GAUGE HEIGHT: 14'-11 1/2" (TO RIM OF 2" DIAMETER BALL VALVE)
LOCATED NEAR CENTER OF TANK

STAR REFERENCE GAUGE HEIGHT: 14'-11 3/4" (TO RIM OF 2" DIAMETER BALL VALVE)
LOCATED NEAR CENTER OF TANK

STAMPED: 7/10/16 REISSUED: 10/01/16 (SUPERSEDES ALL PREVIOUS DATED TABLES TO REFLECT CHANGE IN GAUGE HEIGHT. TANK NOT RESTRAINED)
WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.
INSPECTORATE AMERICA CORPORATION



INSPECTORATE ISO 9002 ACCREDITED

ENTERPRISE MARINE SERVICES LLC
INNAGE TABLE

HULL NO 338

Table with columns: O. FT., 1 FT., 2 FT., 3 FT., 4 FT., 5 FT., 6 FT., 7 FT., 8 FT., 9 FT., 10 FT., 11 FT., 12 FT., 13 FT., 14 FT. Each column contains multiple rows of numerical data representing measurements.

* CAPACITY BELOW STRIKE POINT.

PORT REFERENCE GAUGE HEIGHT:

14'-11 3/4" (TO RIM OF 2" DIAMETER BALL VALVE)

STAR REFERENCE GAUGE HEIGHT: 14'-11 1/2" (TO RIM OF 2" DIAMETER BALL VALVE)

LOCATED NEAR CENTER OF TANK

LOCATED NEAR CENTER OF TANK

STRAPPED: 7/098 REISSUED: 1/2012 (SUSPENSES ALL PREVIOUS DATED TABLES TO REFLECT CHANGE IN GAUGE HEIGHT. TANK NOT RESTRAPPED.)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION



190 9002 ACCREDITED

ENTERPRISE MARINE SERVICES LLC
OUTAGE TABLE

1 PORT

HULL NO. 358

Table with columns for Gauge Height (0 FT. to 14 FT.), Capacity (0 to 24.83), and various gauge readings. Includes a note: 'BARGE SHOULD BE ON EVEN LEVEL, KEEL WHEN GAUGES ARE TAKEN'.

* CAPACITY BELOW STRIKE POINT.

REFERENCE GAUGE HEIGHT:

15'-0" (TO RIM OF 2" DIAMETER BALL VALVE
LOCATED NEAR CENTER OF TANK)

STRAPPED: 7/19/08 REBUSSER: 10/01/12 (SUPERSEDES ALL PREVIOUS
DATED TABLES TO REFLECT CHANGE IN GAUGE HEIGHT. TANK NOT RESTRAPPED)
WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE
IN ACCORDANCE WITH APPLICABLE API STANDARDS AND
ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE

INSPECTORATE AMERICA CORPORATION



ENTERPRISE MARINE SERVICES LLC
OUTAGE TABLE

1 STAR

HULL NO. 338

Table with columns: N, 0 FT., 1 FT., 2 FT., 3 FT., 4 FT., 5 FT., 6 FT., 7 FT., 8 FT., 9 FT., 10 FT., 11 FT., 12 FT., 13 FT., 14 FT. Rows contain numerical data for each gauge height.

INSPECTORATE AMERICA CORPORATION
WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION
DATED TABLES TO REFLECT CHANGE IN GAUGE HEIGHT. TANK NOT RESTRAINED

INSPECTORATE AMERICA CORPORATION
WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.



ENTERPRISE MARINE SERVICES LLC
OUTAGE TABLE

2 PORT

HULL NO. 348

Table with columns: N, O, F, T, 1 FT., 2 FT., 3 FT., 4 FT., 5 FT., 6 FT., 7 FT., 8 FT., 9 FT., 10 FT., 11 FT., 12 FT., 13 FT., 14 FT. Rows represent gauge readings at various heights.

* CAPACITY BELOW STRIKE POINT.

REFERENCE GAUGE HEIGHT:

14'-11 1/2" (TO RIM OF 2" DIAMETER BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION

DATED: 7/26/2012

INSPECTOR



ENTERPRISE MARINE SERVICES LLC OUTAGE TABLE

2 STAR

HULL NO. 358

Table with columns for BARGE SHOULD BE ON EVEN LEVEL, KEEL WHEN GAUGES ARE TAKEN. Columns include gauge numbers (1 FT. to 14 FT.) and corresponding measurements.

CAPACITY BELOW STRIKE POINT:

REFERENCE GAUGE HEIGHT:

14'-11 3/4" TO RIM OF 2" DIAMETER BALL VALVE LOCATED NEAR CENTER OF TANK

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION

DATED 7/26/2020 BY: [Signature]

7/26/2020



ISO 9002 ACCREDITED

INSPECTORATE
BARGE "EMS-328"
ENTERPRISE MARINE SERVICES LLC
OUTAGE TABLE

3 PORT

HULL NO. 338

Table with columns for gauge height (0 FT. to 14 FT.) and corresponding readings for various gauges. Includes a note: 'BARGE SHOULD BE ON EVEN LEVEL, KEEL WHEN GAUGES ARE TAKEN'.

* CAPACITY BELOW STRIKE POINT.

REFERENCE GAUGE HEIGHT:

14'-11 3/4" (TO RIM OF 2" DIAMETER BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 7/068 REISSUED: 12/012 (SUSPENDED ALL PREVIOUS DATED TABLES TO REFLECT CHANGE IN GAUGE HEIGHT. TANK NOT RESTRAPPED)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION



BARGE "EMS-328" ENTERPRISE MARINE SERVICES LLC OUTAGE TABLE

3 STAR

HULL NO. 398

Table with columns for M, O, FT., 1 FT., 2 FT., 3 FT., 4 FT., 5 FT., 6 FT., 7 FT., 8 FT., 9 FT., 10 FT., 11 FT., 12 FT., 13 FT., 14 FT. and rows for various measurements.

* CAPACITY BELOW STRIKE POINT:

REFERENCE GAUGE HEIGHT:

14'-11 1/2" TO RIM OF 2" DIAMETER BALL VALVE LOCATED NEAR CENTER OF TANK

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE

INSPECTORATE AMERICA CORPORATION

Signature

STRAPPED: 7/10/06 RESSUES: 17/09/12 (SUPERSEDES ALL PREVIOUS DATED TABLES TO REFLECT CHANGE IN GAUGE HEIGHT. TANK NOT RESTRAPPED)