



EMS 325

OUTGAGE TABLE

1 STAR

BARGE SHOULD BE ON EVEN LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 335

Table with 15 columns (0 FT. to 14 FT.) and 34 rows. Each cell contains gauge height and deviation data.

REFERENCE GAUGE HEIGHT: 15'-0" TO RIM OF BALL VALVE LOCATED NEAR CENTER OF TANK

STRAPPED: 2/96 REISSUED: 2/2005 (SUPERSEDES ALL PREVIOUS DATED TABLES TO REFLECT BALL VALVE GAUGING) TANK NOT RESTRAPPED.

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION

[Signature]



EMS 325

OUTGAGE TABLE

HULL NO. 335

| CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS | | CAPACITY BELOW STRIKE POINT | | REFERENCE GAUGE HEIGHT : 14-11 3/4" (TO RIM OF BALL VALVE LOCATED NEAR CENTER OF TANK) | | | | | | | | | | | |
|--|----------|-----------------------------|----------|--|----------|----------|----------|----------|----------|----------|----------|----------|----------|--------|--------|
| W | 0 FT. | 1 FT. | 2 FT. | 3 FT. | 4 FT. | 5 FT. | 6 FT. | 7 FT. | 8 FT. | 9 FT. | 10 FT. | 11 FT. | 12 FT. | 13 FT. | 14 FT. |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 1 | 5,151.29 | 4,825.93 | 4,500.57 | 4,175.21 | 3,849.85 | 3,524.49 | 3,199.13 | 2,873.77 | 2,548.41 | 2,222.95 | 1,897.59 | 1,572.23 | 1,246.87 | 921.51 | 596.15 |
| 2 | 5,151.29 | 4,825.93 | 4,500.57 | 4,175.21 | 3,849.85 | 3,524.49 | 3,199.13 | 2,873.77 | 2,548.41 | 2,222.95 | 1,897.59 | 1,572.23 | 1,246.87 | 921.51 | 596.15 |
| 3 | 5,151.29 | 4,825.93 | 4,500.57 | 4,175.21 | 3,849.85 | 3,524.49 | 3,199.13 | 2,873.77 | 2,548.41 | 2,222.95 | 1,897.59 | 1,572.23 | 1,246.87 | 921.51 | 596.15 |
| 4 | 5,151.29 | 4,825.93 | 4,500.57 | 4,175.21 | 3,849.85 | 3,524.49 | 3,199.13 | 2,873.77 | 2,548.41 | 2,222.95 | 1,897.59 | 1,572.23 | 1,246.87 | 921.51 | 596.15 |
| 5 | 5,151.29 | 4,825.93 | 4,500.57 | 4,175.21 | 3,849.85 | 3,524.49 | 3,199.13 | 2,873.77 | 2,548.41 | 2,222.95 | 1,897.59 | 1,572.23 | 1,246.87 | 921.51 | 596.15 |
| 6 | 5,151.29 | 4,825.93 | 4,500.57 | 4,175.21 | 3,849.85 | 3,524.49 | 3,199.13 | 2,873.77 | 2,548.41 | 2,222.95 | 1,897.59 | 1,572.23 | 1,246.87 | 921.51 | 596.15 |
| 7 | 5,151.29 | 4,825.93 | 4,500.57 | 4,175.21 | 3,849.85 | 3,524.49 | 3,199.13 | 2,873.77 | 2,548.41 | 2,222.95 | 1,897.59 | 1,572.23 | 1,246.87 | 921.51 | 596.15 |
| 8 | 5,151.29 | 4,825.93 | 4,500.57 | 4,175.21 | 3,849.85 | 3,524.49 | 3,199.13 | 2,873.77 | 2,548.41 | 2,222.95 | 1,897.59 | 1,572.23 | 1,246.87 | 921.51 | 596.15 |
| 9 | 5,151.29 | 4,825.93 | 4,500.57 | 4,175.21 | 3,849.85 | 3,524.49 | 3,199.13 | 2,873.77 | 2,548.41 | 2,222.95 | 1,897.59 | 1,572.23 | 1,246.87 | 921.51 | 596.15 |
| 10 | 5,151.29 | 4,825.93 | 4,500.57 | 4,175.21 | 3,849.85 | 3,524.49 | 3,199.13 | 2,873.77 | 2,548.41 | 2,222.95 | 1,897.59 | 1,572.23 | 1,246.87 | 921.51 | 596.15 |
| 11 | 5,151.29 | 4,825.93 | 4,500.57 | 4,175.21 | 3,849.85 | 3,524.49 | 3,199.13 | 2,873.77 | 2,548.41 | 2,222.95 | 1,897.59 | 1,572.23 | 1,246.87 | 921.51 | 596.15 |
| 12 | 5,151.29 | 4,825.93 | 4,500.57 | 4,175.21 | 3,849.85 | 3,524.49 | 3,199.13 | 2,873.77 | 2,548.41 | 2,222.95 | 1,897.59 | 1,572.23 | 1,246.87 | 921.51 | 596.15 |
| 13 | 5,151.29 | 4,825.93 | 4,500.57 | 4,175.21 | 3,849.85 | 3,524.49 | 3,199.13 | 2,873.77 | 2,548.41 | 2,222.95 | 1,897.59 | 1,572.23 | 1,246.87 | 921.51 | 596.15 |
| 14 | 5,151.29 | 4,825.93 | 4,500.57 | 4,175.21 | 3,849.85 | 3,524.49 | 3,199.13 | 2,873.77 | 2,548.41 | 2,222.95 | 1,897.59 | 1,572.23 | 1,246.87 | 921.51 | 596.15 |

STRAPPED: 2/1996 REISSUED : 2/2205 (SUPERCSEDS ALL PREVIOUS DATED TABLES TO REFLECT BALL VALVE GAUGING) TANK NOT RESTRAINED.

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION



EMS 325

OUTAGE TABLE

2 STAR

HULL NO. 395

| CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS | | CAPACITY BELOW STRIKE POINT | | REFERENCE GAUGE HEIGHT: 15'-0" TO RIM OF BALL VALVE LOCATED NEAR CENTER OF TANK | | | | | | | | | | |
|--|-------|-----------------------------|-------|---|-------|-------|-------|-------|-------|--------|--------|--------|--------|--------|
| 0 FT. | 1 FT. | 2 FT. | 3 FT. | 4 FT. | 5 FT. | 6 FT. | 7 FT. | 8 FT. | 9 FT. | 10 FT. | 11 FT. | 12 FT. | 13 FT. | 14 FT. |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 |
| 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 | 3 |
| 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 |
| 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 | 5 |
| 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 | 6 |
| 7 | 7 | 7 | 7 | 7 | 7 | 7 | 7 | 7 | 7 | 7 | 7 | 7 | 7 | 7 |
| 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 |
| 9 | 9 | 9 | 9 | 9 | 9 | 9 | 9 | 9 | 9 | 9 | 9 | 9 | 9 | 9 |
| 10 | 10 | 10 | 10 | 10 | 10 | 10 | 10 | 10 | 10 | 10 | 10 | 10 | 10 | 10 |
| 11 | 11 | 11 | 11 | 11 | 11 | 11 | 11 | 11 | 11 | 11 | 11 | 11 | 11 | 11 |
| 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 12 |
| 13 | 13 | 13 | 13 | 13 | 13 | 13 | 13 | 13 | 13 | 13 | 13 | 13 | 13 | 13 |
| 14 | 14 | 14 | 14 | 14 | 14 | 14 | 14 | 14 | 14 | 14 | 14 | 14 | 14 | 14 |
| 15 | 15 | 15 | 15 | 15 | 15 | 15 | 15 | 15 | 15 | 15 | 15 | 15 | 15 | 15 |

STRAPPED: 2/1996 REISSUED: 2/2005 (SUPERSEDES ALL PREVIOUS DATED TABLES TO REFLECT BALL VALVE GAUGING) TANK NOT RESTRAPPED.

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

[Signature]

INSPECTORIAL AMERICA CORPORATION



EMS 325

OUTAGE TABLE

3 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 335

| CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS | | REFERENCE GAUGE HEIGHT : 15'-0" (TO RIM OF BALL VALVE LOCATED NEAR CENTER OF TANK) | | | | | | | | | | | | | |
|--|----------|--|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|--------|--------|--|
| 0 FT. | 1 FT. | 2 FT. | 3 FT. | 4 FT. | 5 FT. | 6 FT. | 7 FT. | 8 FT. | 9 FT. | 10 FT. | 11 FT. | 12 FT. | 13 FT. | 14 FT. | |
| 0 | 4,525.32 | 4,334.56 | 4,105.48 | 3,876.62 | 3,647.76 | 3,389.90 | 2,996.47 | 2,637.05 | 2,295.62 | 1,984.20 | 1,512.78 | 1,144.35 | 789.93 | 388.50 | |
| 1 | 4,525.32 | 4,334.56 | 4,105.48 | 3,876.62 | 3,647.76 | 3,389.90 | 2,996.47 | 2,637.05 | 2,295.62 | 1,984.20 | 1,512.78 | 1,144.35 | 789.93 | 388.50 | |
| 2 | 4,525.32 | 4,334.56 | 4,105.48 | 3,876.62 | 3,647.76 | 3,389.90 | 2,996.47 | 2,637.05 | 2,295.62 | 1,984.20 | 1,512.78 | 1,144.35 | 789.93 | 388.50 | |
| 3 | 4,525.32 | 4,334.56 | 4,105.48 | 3,876.62 | 3,647.76 | 3,389.90 | 2,996.47 | 2,637.05 | 2,295.62 | 1,984.20 | 1,512.78 | 1,144.35 | 789.93 | 388.50 | |
| 4 | 4,525.32 | 4,334.56 | 4,105.48 | 3,876.62 | 3,647.76 | 3,389.90 | 2,996.47 | 2,637.05 | 2,295.62 | 1,984.20 | 1,512.78 | 1,144.35 | 789.93 | 388.50 | |
| 5 | 4,525.32 | 4,334.56 | 4,105.48 | 3,876.62 | 3,647.76 | 3,389.90 | 2,996.47 | 2,637.05 | 2,295.62 | 1,984.20 | 1,512.78 | 1,144.35 | 789.93 | 388.50 | |
| 6 | 4,525.32 | 4,334.56 | 4,105.48 | 3,876.62 | 3,647.76 | 3,389.90 | 2,996.47 | 2,637.05 | 2,295.62 | 1,984.20 | 1,512.78 | 1,144.35 | 789.93 | 388.50 | |
| 7 | 4,525.32 | 4,334.56 | 4,105.48 | 3,876.62 | 3,647.76 | 3,389.90 | 2,996.47 | 2,637.05 | 2,295.62 | 1,984.20 | 1,512.78 | 1,144.35 | 789.93 | 388.50 | |
| 8 | 4,525.32 | 4,334.56 | 4,105.48 | 3,876.62 | 3,647.76 | 3,389.90 | 2,996.47 | 2,637.05 | 2,295.62 | 1,984.20 | 1,512.78 | 1,144.35 | 789.93 | 388.50 | |
| 9 | 4,525.32 | 4,334.56 | 4,105.48 | 3,876.62 | 3,647.76 | 3,389.90 | 2,996.47 | 2,637.05 | 2,295.62 | 1,984.20 | 1,512.78 | 1,144.35 | 789.93 | 388.50 | |
| 10 | 4,525.32 | 4,334.56 | 4,105.48 | 3,876.62 | 3,647.76 | 3,389.90 | 2,996.47 | 2,637.05 | 2,295.62 | 1,984.20 | 1,512.78 | 1,144.35 | 789.93 | 388.50 | |
| 11 | 4,525.32 | 4,334.56 | 4,105.48 | 3,876.62 | 3,647.76 | 3,389.90 | 2,996.47 | 2,637.05 | 2,295.62 | 1,984.20 | 1,512.78 | 1,144.35 | 789.93 | 388.50 | |
| 12 | 4,525.32 | 4,334.56 | 4,105.48 | 3,876.62 | 3,647.76 | 3,389.90 | 2,996.47 | 2,637.05 | 2,295.62 | 1,984.20 | 1,512.78 | 1,144.35 | 789.93 | 388.50 | |
| 13 | 4,525.32 | 4,334.56 | 4,105.48 | 3,876.62 | 3,647.76 | 3,389.90 | 2,996.47 | 2,637.05 | 2,295.62 | 1,984.20 | 1,512.78 | 1,144.35 | 789.93 | 388.50 | |
| 14 | 4,525.32 | 4,334.56 | 4,105.48 | 3,876.62 | 3,647.76 | 3,389.90 | 2,996.47 | 2,637.05 | 2,295.62 | 1,984.20 | 1,512.78 | 1,144.35 | 789.93 | 388.50 | |
| 15 | 4,525.32 | 4,334.56 | 4,105.48 | 3,876.62 | 3,647.76 | 3,389.90 | 2,996.47 | 2,637.05 | 2,295.62 | 1,984.20 | 1,512.78 | 1,144.35 | 789.93 | 388.50 | |

STRAPPED: 20/96 REISSUED: 2/22/05 (SUPERSEDES ALL PREVIOUS DATED TABLES TO REFLECT BALL VALVE GAUGING TANK NOT RESTRAPPED).

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORIAL AMERICA CORPORATION