



EMS 323
Enterprise Marine Services LLC

TANK NO. 1
PORT

OUTGATE TABLE

HULL NO. 330

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

14 FT.	13 FT.	12 FT.	11 FT.	10 FT.	9 FT.	8 FT.	7 FT.	6 FT.	5 FT.	4 FT.	3 FT.	2 FT.	1 FT.	0 FT.
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
2	2	2	2	2	2	2	2	2	2	2	2	2	2	2
3	3	3	3	3	3	3	3	3	3	3	3	3	3	3
4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
5	5	5	5	5	5	5	5	5	5	5	5	5	5	5
6	6	6	6	6	6	6	6	6	6	6	6	6	6	6
7	7	7	7	7	7	7	7	7	7	7	7	7	7	7
8	8	8	8	8	8	8	8	8	8	8	8	8	8	8
9	9	9	9	9	9	9	9	9	9	9	9	9	9	9
10	10	10	10	10	10	10	10	10	10	10	10	10	10	10
11	11	11	11	11	11	11	11	11	11	11	11	11	11	11
12	12	12	12	12	12	12	12	12	12	12	12	12	12	12
13	13	13	13	13	13	13	13	13	13	13	13	13	13	13
14	14	14	14	14	14	14	14	14	14	14	14	14	14	14

STRAPPED: 9/18/95

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE

INSPECTORATE AMERICA CORPORATION

REFERENCE GAUGE HEIGHT: 14'-11 3/4" (RIM OF 2" DIAMETER BALL VALVE LOCATED NEAR CENTER OF TANK)

* CAPACITY BELOW STRIKE POINT

CAPACITIES GIVEN IN BARRELS OF 42 US GALLONS



EMS 323 Enterprise Marine Services LLC

TANK NO. 1 STAR

HULL NO. 330

OUTGAGE TABLE

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

Table with columns for Gauge (0 to 15), Height (0 FT. to 15 FT.), and Volume (0 to 36,681). Rows 0-15 correspond to gauges 0 through 15. The table provides volume data for each gauge height and includes a total volume for the tank.

REFERENCE GAUGE HEIGHT : 15'-0" (RIM OF 2" DIAMETER BALL VALVE LOCATED NEAR CENTER OF TANK)

* CAPACITY BELOW STRIKE POINT CAPACITIES GIVEN IN BARRELS OF 42 US GALLONS

STRAPPED: 9/18/05

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE

Inspector Signature

INSPECTORATE AMERICA CORPORATION



EMS 323

Enterprise Marine Services LLC

TANK NO. 2
PORT

OUTAGE TABLE

BARGE SHOULD BE ON EVEN LEVEL KEEL WHEN GAUGES ARE TAKEN

0 FT.		1 FT.		2 FT.		3 FT.		4 FT.		5 FT.		7 FT.		8 FT.		9 FT.		10 FT.		11 FT.		12 FT.		13 FT.		14 FT.		15 FT.		
N	0	N	0	N	0	N	0	N	0	N	0	N	0	N	0	N	0	N	0	N	0	N	0	N	0	N	0	N	0	
1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4	
3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4	
1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	
2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	
3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	
4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	
5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	
6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	
7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	
8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	
9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	
10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	
11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	
12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12
13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13
14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14
15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15

STRAPPED: 9/18/95

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE

INSPECTORATE AMERICA CORPORATION

REFERENCE GAUGE HEIGHT: 15'-0" (RIM OF 2" DIAMETER BALL VALVE LOCATED NEAR CENTER OF TANK)

* CAPACITY BELOW STRIKE POINT

CAPACITIES GIVEN IN BARRELS OF 42 US GALLONS



EMS 323 Enterprise Marine Services LLC

TANK NO. 2 STAR

OUTGATE TABLE

HULL NO. 330

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

Table with columns for gauge height (0 FT. to 14 FT.), diameter ball valve, and capacity below strike point. Includes a vertical note on the right: 'CAPACITY BELOW STRIKE POINT * CAPACITY GREEN BARRELS OR 42 US GALLONS'.

REFERENCE GAUGE HEIGHT: 14'-11 3/4" RIM OF 2" DIAMETER BALL VALVE LOCATED NEAR CENTER OF TANK

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE

Inspector signature and 'INSPECTORATE AMERICA CORPORATION' logo

STRAPPED: 9/18/95



EMS 323
Enterprise Marine Services LLC

TANK NO. 3
STAR

OUTAGE TABLE

HULL NO. 330

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

0 FT.	1 FT.	2 FT.	3 FT.	4 FT.	5 FT.	6 FT.	7 FT.	8 FT.	9 FT.	10 FT.	11 FT.	12 FT.	13 FT.	14 FT.
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
2	2	2	2	2	2	2	2	2	2	2	2	2	2	2
3	3	3	3	3	3	3	3	3	3	3	3	3	3	3
4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
5	5	5	5	5	5	5	5	5	5	5	5	5	5	5
6	6	6	6	6	6	6	6	6	6	6	6	6	6	6
7	7	7	7	7	7	7	7	7	7	7	7	7	7	7
8	8	8	8	8	8	8	8	8	8	8	8	8	8	8
9	9	9	9	9	9	9	9	9	9	9	9	9	9	9
10	10	10	10	10	10	10	10	10	10	10	10	10	10	10
11	11	11	11	11	11	11	11	11	11	11	11	11	11	11
12	12	12	12	12	12	12	12	12	12	12	12	12	12	12
13	13	13	13	13	13	13	13	13	13	13	13	13	13	13
14	14	14	14	14	14	14	14	14	14	14	14	14	14	14
15	15	15	15	15	15	15	15	15	15	15	15	15	15	15
16	16	16	16	16	16	16	16	16	16	16	16	16	16	16
17	17	17	17	17	17	17	17	17	17	17	17	17	17	17
18	18	18	18	18	18	18	18	18	18	18	18	18	18	18
19	19	19	19	19	19	19	19	19	19	19	19	19	19	19
20	20	20	20	20	20	20	20	20	20	20	20	20	20	20
21	21	21	21	21	21	21	21	21	21	21	21	21	21	21
22	22	22	22	22	22	22	22	22	22	22	22	22	22	22
23	23	23	23	23	23	23	23	23	23	23	23	23	23	23
24	24	24	24	24	24	24	24	24	24	24	24	24	24	24
25	25	25	25	25	25	25	25	25	25	25	25	25	25	25
26	26	26	26	26	26	26	26	26	26	26	26	26	26	26
27	27	27	27	27	27	27	27	27	27	27	27	27	27	27
28	28	28	28	28	28	28	28	28	28	28	28	28	28	28
29	29	29	29	29	29	29	29	29	29	29	29	29	29	29
30	30	30	30	30	30	30	30	30	30	30	30	30	30	30
31	31	31	31	31	31	31	31	31	31	31	31	31	31	31
32	32	32	32	32	32	32	32	32	32	32	32	32	32	32
33	33	33	33	33	33	33	33	33	33	33	33	33	33	33
34	34	34	34	34	34	34	34	34	34	34	34	34	34	34

STRAPPED: 9/18/95

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE

[Signature]
INSPECTORATE AMERICA CORPORATION

REFERENCE GAUGE HEIGHT: 14'-11 3/4" (RIM OF 2" DIAMETER BALL VALVE LOCATED NEAR CENTER OF TANK)

* CAPACITY BELOW STRIKE POINT

CAPACITIES GIVEN IN BARRELS OF 42 US GALLONS