



BARGE "CTCo-367 B"
CENAC TOWING COMPANY

INNAGE TABLE

TANK NO. 1
PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2173-2

Table with columns for height (0 FT. to 14 FT.) and corresponding capacity values for various gauge heights (0, 1/4, 1/2, 3/4).

CAPACITIES GIVEN IN BARRELS OF 42 US GALLONS

STRAPPED: 11/20/07

\* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 14'-9" (TO RIM OF 2" DIAMETER PIPE
LOCATED 14' FROM CENTERLINE OF BARGE)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE
IN ACCORDANCE WITH APPLICABLE API STANDARDS AND
ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature

INSPECTORATE AMERICA CORPORATION





BARGE "CTCo-367 B" CENAC TOWING COMPANY

INNAGE TABLE

TANK NO. 3 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2173-2

Table with 15 columns (0 FT. to 14 FT.) and multiple rows of capacity data for various gauge heights (0, 1/4, 1/2, 3/4).

CAPACITIES GIVEN IN BARRELS OF 42 US GALLONS

STRAPPED: 11/21/07

\* CAPACITY BELOW STRIKE POINT

PORT REFERENCE GAUGE HEIGHT: 14'-8 1/4" (TO RIM OF 2" DIAMETER PIPE LOCATED 14' FROM CENTERLINE OF BARGE)

STAR REFERENCE GAUGE HEIGHT: 14'-8" (TO RIM OF 2" DIAMETER PIPE LOCATED 14' FROM CENTERLINE OF BARGE)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature of the inspector

INSPECTORATE AMERICA CORPORATION



# BARGE "CTCo-367 B"

## CENAC TOWING COMPANY

HULL NO. 2173-2

CORRECTION TABLE FOR TRIM AFT.

### FOR OUTAGE GAUGES ONLY

TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.
0'-6"	NIL	NIL	NIL
1'-0"	NIL	NIL	NIL
1'-6"	NIL	NIL	NIL
2'-0"	(-) 0' - 0 1/8"	(-) 0' - 0 1/8"	(-) 0' - 0 1/8"
2'-6"	(-) 0' - 0 1/8"	(-) 0' - 0 1/8"	(-) 0' - 0 1/8"
3'-0"	(-) 0' - 0 1/8"	(-) 0' - 0 1/8"	(-) 0' - 0 1/8"
3'-6"	(-) 0' - 0 1/8"	(-) 0' - 0 1/8"	(-) 0' - 0 1/8"
4'-0"	(-) 0' - 0 1/8"	(-) 0' - 0 1/8"	(-) 0' - 0 1/8"
4'-6"	(-) 0' - 0 1/8"	(-) 0' - 0 1/8"	(-) 0' - 0 1/8"
5'-0"	(-) 0' - 0 1/4"	(-) 0' - 0 1/4"	(-) 0' - 0 1/4"

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED, TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "INNAGE" GAUGES, REVERSE SIGNS.

DATE: 11/2/07

BY:

INSPECTORATE AMERICA CORPORATION