



INSPECTORATE

BARGE "EMS-324"
ENTERPRISE MARINE SERVICES, LLC
 OUTAGE TABLE

BARGE SHOULD BE ON EVEN LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 334

TANK NO. 1
PORT OR STAR

IN	0 FT.	1 FT.	2 FT.	3 FT.	4 FT.	5 FT.	6 FT.	7 FT.	8 FT.	9 FT.	10 FT.	11 FT.	12 FT.	13 FT.	14 FT.
0	5134.51	4818.40	4444.23	4080.07	3716.90	3354.73	2992.56	2630.39	2268.22	1906.05	1543.88	1181.71	819.54	457.37	91.20
1	5132.61	4816.50	4442.33	4078.17	3715.00	3352.83	2989.66	2627.49	2265.32	1903.15	1541.98	1179.81	817.64	455.46	72.30
2	5130.72	4814.60	4440.43	4076.27	3713.10	3350.93	2987.76	2625.59	2263.42	1901.25	1540.08	1177.91	815.74	453.56	53.40
3	5128.83	4812.70	4438.53	4074.37	3711.20	3349.03	2985.86	2623.69	2261.52	1899.35	1538.18	1176.01	813.84	451.66	34.50
4	5126.94	4810.80	4436.63	4072.47	3709.30	3347.13	2983.96	2621.79	2259.62	1897.45	1536.28	1174.11	811.94	449.76	15.60
5	5125.05	4808.90	4434.73	4070.57	3707.40	3345.23	2982.06	2619.89	2257.72	1895.55	1534.38	1172.21	810.04	447.86	-3.30
6	5123.16	4807.00	4432.83	4068.67	3705.50	3343.33	2980.16	2617.99	2255.82	1893.65	1532.48	1170.31	808.14	445.96	-24.40
7	5121.27	4805.10	4430.93	4066.77	3703.60	3341.43	2978.26	2616.09	2253.92	1891.75	1530.58	1168.41	806.24	444.06	-45.50
8	5119.38	4803.20	4429.03	4064.87	3701.70	3339.53	2976.36	2614.19	2252.02	1889.85	1528.68	1166.51	804.34	442.16	-66.60
9	5117.49	4801.30	4427.13	4062.97	3699.80	3337.63	2974.46	2612.29	2250.12	1887.95	1526.78	1164.61	802.44	440.26	-87.70
10	5115.60	4799.40	4425.23	4061.07	3697.90	3335.73	2972.56	2610.39	2248.22	1886.05	1524.88	1162.71	800.54	438.36	-108.80
11	5113.71	4797.50	4423.33	4059.17	3696.00	3333.83	2970.66	2608.49	2246.32	1884.15	1522.98	1160.81	798.64	436.46	-129.90
12	5111.82	4795.60	4421.43	4057.27	3694.10	3331.93	2968.76	2606.59	2244.42	1882.25	1521.08	1158.91	796.74	434.56	-151.00
13	5109.93	4793.70	4419.53	4055.37	3692.20	3330.03	2966.86	2604.69	2242.52	1880.35	1519.18	1157.01	794.84	432.66	-172.10
14	5108.04	4791.80	4417.63	4053.47	3690.30	3328.13	2964.96	2602.79	2240.62	1878.45	1517.28	1155.11	792.94	430.76	-193.20
15	5106.15	4789.90	4415.73	4051.57	3688.40	3326.23	2963.06	2600.89	2238.72	1876.55	1515.38	1153.21	791.04	428.86	-214.30

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-0" (TO RIM OF 2" DIAMETER BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 22795

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION



INSPECTORATE

BARGE "EMS-324"
ENTERPRISE MARINE SERVICES, LLC
OUTAGE TABLE

BARGE SHOULD BE ON EVEN LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 334

TANK NO. 2
PORT OR STAR

Table with columns for Gauge No., Gauge Type (0 FT., 1 FT., 2 FT., 3 FT., 4 FT., 5 FT., 6 FT., 7 FT., 8 FT., 9 FT., 10 FT., 11 FT., 12 FT., 13 FT., 14 FT.), and Gauge Reading. The table contains multiple rows of data for various gauges across different tanks.

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 15'-0" TO RIM OF 2" DIAMETER BALL VALVE
LOCATED NEAR CENTER OF TANK

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE
IN ACCORDANCE WITH APPLICABLE API STANDARDS AND
ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION

STRAPPED: 22095



INSPECTORATE

BARGE "EMS-324"
ENTERPRISE MARINE SERVICES, LLC
 OUTAGE TABLE

BARGE SHOULD BE ON EVEN LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 334

CAPACITY BELOW STRIKE POINT		REFERENCE GAUGE HEIGHT: 15'-0" TO RIM OF 2" DIAMETER BALL VALVE LOCATED NEAR CENTER OF TANK		TANK NO. 3		PORT OR STAR	
IN	OUT	IN	OUT	IN	OUT	IN	OUT
0	0	0	0	0	0	0	0
1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/4
1/2	1/2	1/2	1/2	1/2	1/2	1/2	1/2
3/4	3/4	3/4	3/4	3/4	3/4	3/4	3/4
1	1	1	1	1	1	1	1
1 1/4	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4	1 1/4
1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2
1 3/4	1 3/4	1 3/4	1 3/4	1 3/4	1 3/4	1 3/4	1 3/4
2	2	2	2	2	2	2	2
2 1/4	2 1/4	2 1/4	2 1/4	2 1/4	2 1/4	2 1/4	2 1/4
2 1/2	2 1/2	2 1/2	2 1/2	2 1/2	2 1/2	2 1/2	2 1/2
2 3/4	2 3/4	2 3/4	2 3/4	2 3/4	2 3/4	2 3/4	2 3/4
3	3	3	3	3	3	3	3
3 1/4	3 1/4	3 1/4	3 1/4	3 1/4	3 1/4	3 1/4	3 1/4
3 1/2	3 1/2	3 1/2	3 1/2	3 1/2	3 1/2	3 1/2	3 1/2
3 3/4	3 3/4	3 3/4	3 3/4	3 3/4	3 3/4	3 3/4	3 3/4
4	4	4	4	4	4	4	4
4 1/4	4 1/4	4 1/4	4 1/4	4 1/4	4 1/4	4 1/4	4 1/4
4 1/2	4 1/2	4 1/2	4 1/2	4 1/2	4 1/2	4 1/2	4 1/2
4 3/4	4 3/4	4 3/4	4 3/4	4 3/4	4 3/4	4 3/4	4 3/4
5	5	5	5	5	5	5	5
5 1/4	5 1/4	5 1/4	5 1/4	5 1/4	5 1/4	5 1/4	5 1/4
5 1/2	5 1/2	5 1/2	5 1/2	5 1/2	5 1/2	5 1/2	5 1/2
5 3/4	5 3/4	5 3/4	5 3/4	5 3/4	5 3/4	5 3/4	5 3/4
6	6	6	6	6	6	6	6
6 1/4	6 1/4	6 1/4	6 1/4	6 1/4	6 1/4	6 1/4	6 1/4
6 1/2	6 1/2	6 1/2	6 1/2	6 1/2	6 1/2	6 1/2	6 1/2
6 3/4	6 3/4	6 3/4	6 3/4	6 3/4	6 3/4	6 3/4	6 3/4
7	7	7	7	7	7	7	7
7 1/4	7 1/4	7 1/4	7 1/4	7 1/4	7 1/4	7 1/4	7 1/4
7 1/2	7 1/2	7 1/2	7 1/2	7 1/2	7 1/2	7 1/2	7 1/2
7 3/4	7 3/4	7 3/4	7 3/4	7 3/4	7 3/4	7 3/4	7 3/4
8	8	8	8	8	8	8	8
8 1/4	8 1/4	8 1/4	8 1/4	8 1/4	8 1/4	8 1/4	8 1/4
8 1/2	8 1/2	8 1/2	8 1/2	8 1/2	8 1/2	8 1/2	8 1/2
8 3/4	8 3/4	8 3/4	8 3/4	8 3/4	8 3/4	8 3/4	8 3/4
9	9	9	9	9	9	9	9
9 1/4	9 1/4	9 1/4	9 1/4	9 1/4	9 1/4	9 1/4	9 1/4
9 1/2	9 1/2	9 1/2	9 1/2	9 1/2	9 1/2	9 1/2	9 1/2
9 3/4	9 3/4	9 3/4	9 3/4	9 3/4	9 3/4	9 3/4	9 3/4
10	10	10	10	10	10	10	10
10 1/4	10 1/4	10 1/4	10 1/4	10 1/4	10 1/4	10 1/4	10 1/4
10 1/2	10 1/2	10 1/2	10 1/2	10 1/2	10 1/2	10 1/2	10 1/2
10 3/4	10 3/4	10 3/4	10 3/4	10 3/4	10 3/4	10 3/4	10 3/4
11	11	11	11	11	11	11	11
11 1/4	11 1/4	11 1/4	11 1/4	11 1/4	11 1/4	11 1/4	11 1/4
11 1/2	11 1/2	11 1/2	11 1/2	11 1/2	11 1/2	11 1/2	11 1/2
11 3/4	11 3/4	11 3/4	11 3/4	11 3/4	11 3/4	11 3/4	11 3/4
12	12	12	12	12	12	12	12
12 1/4	12 1/4	12 1/4	12 1/4	12 1/4	12 1/4	12 1/4	12 1/4
12 1/2	12 1/2	12 1/2	12 1/2	12 1/2	12 1/2	12 1/2	12 1/2
12 3/4	12 3/4	12 3/4	12 3/4	12 3/4	12 3/4	12 3/4	12 3/4
13	13	13	13	13	13	13	13
13 1/4	13 1/4	13 1/4	13 1/4	13 1/4	13 1/4	13 1/4	13 1/4
13 1/2	13 1/2	13 1/2	13 1/2	13 1/2	13 1/2	13 1/2	13 1/2
13 3/4	13 3/4	13 3/4	13 3/4	13 3/4	13 3/4	13 3/4	13 3/4
14	14	14	14	14	14	14	14
14 1/4	14 1/4	14 1/4	14 1/4	14 1/4	14 1/4	14 1/4	14 1/4
14 1/2	14 1/2	14 1/2	14 1/2	14 1/2	14 1/2	14 1/2	14 1/2
14 3/4	14 3/4	14 3/4	14 3/4	14 3/4	14 3/4	14 3/4	14 3/4
15	15	15	15	15	15	15	15

STRAPPED: 27296

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTOR/ATE AMERICA CORPORATION



INSPECTORATE

ENTERPRISE MARINE SERVICES, LLC
BARGE "EMS-324"
INNAGE TABLE

TANK NO. 1
PORT OR STAR

HULL NO 334

Table with columns: O FT., M, 1 FT., M, 2 FT., M, 3 FT., M, 4 FT., M, 5 FT., M, 6 FT., M, 7 FT., M, 8 FT., M, 9 FT., M, 10 FT., M, 11 FT., M, 12 FT., M, 13 FT., M, 14 FT., M. Rows contain numerical data for each measurement point.

CAPACITIES GIVEN IN BARRELS OF 42 US GALLONS

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 15'-0" (TO RIM OF 2" DIAMETER BALL VALVE LOCATED NEAR CENTER OF TANK)

STRAPPED: 2796

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION



INSPECTOR'S

INSPECTOR'S

HULL NO 183

BARGE "EMS-324"
ENTERPRISE MARINE SERVICES, LLC
INNAGE TABLE

TANK NO. 2
PORT OR STAR

Table with columns: O.F.T., 1.F.T., 2.F.T., 3.F.T., 4.F.T., 5.F.T., 6.F.T., 7.F.T., 8.F.T., 9.F.T., 10.F.T., 11.F.T., 12.F.T., 13.F.T., 14.F.T. and rows for various tank measurements.

* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT: 15'-0" (TO RIM OF 2" DIAMETER BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION

STRAPPED: 2298



ENTERPRISE MARINE SERVICES, LLC

BARGE "EMS-324"
ENTERPRISE MARINE SERVICES, LLC
INNAGE TABLE

TANK NO. 3
PORT OR STAR

HULL NO. 103

Table with columns: W, D, 0 FT., 1 FT., 2 FT., 3 FT., 4 FT., 5 FT., 6 FT., 7 FT., 8 FT., 9 FT., 10 FT., 11 FT., 12 FT., 13 FT., 14 FT. and rows for various measurements and capacities.

CAPACITIES GIVEN IN BARRELS OF 42 US GALLONS
CAPACITY BELOW STRIKE POINT
REFERENCE GAUGE HEIGHT: 15'-0" (TO RIM OF 2" DIAMETER BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.
INSPECTOR: AMERICA CORPORATION