



INSPECTORATE

BARGE "TMS-450"
TEPPCO MARINE SERVICE.

TANK NO.
PORT

Capacities in Barrels

Page 1 of 2

Table with 10 columns (0 FEET to 9 FEET) and 34 rows. Each cell contains numerical values representing capacities in barrels at specific depths and intervals.

NOTE: TABLE SCALED FROM EXTREME BOTTOM OF TANK.
BARGE SHOULD BE ON EVEN KEEL, WHEN GAUGING.

CAPACITIES REFLECT EXPANSION OF TANK SHELL
FOR AN OPERATING TEMPERATURE OF 60 F.

INNAGE TABLE

STRAPPED: 3/17/09
WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE
IN ACCORDANCE WITH APPLICABLE API STANDARDS AND
ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION



INSPECTORATE

ISO 9002 ACCREDITED

BARGE "TMS-450"

TEPPCO MARINE SERVICE.

TANK NO.

PORT

Capacities in Barrels

Page 2 of 2

	10 FEET	11 FEET	12 FEET	13 FEET	14 FEET	15 FEET	16 FEET	17 FEET	18 FEET	19 FEET
0	4,858.06	5,453.40	6,042.51	6,580.73	7,102.78	7,554.12	7,947.77	8,246.51	0	0
1/4	4,870.59	5,465.64	6,052.51	6,591.83	7,102.96	7,563.08	7,955.08	8,251.39	1/4	1/4
1/2	4,883.11	5,477.87	6,054.27	6,602.90	7,113.11	7,572.01	7,962.36	8,256.20	1/2	1/2
3/4	4,895.63	5,490.10	6,066.02	6,613.96	7,123.25	7,580.91	7,969.60	8,260.95	3/4	3/4
1	4,908.14	5,502.32	6,077.75	6,625.01	7,133.36	7,589.79	7,976.79	8,265.63	1	1
1/4	4,920.66	5,514.53	6,089.48	6,636.03	7,143.44	7,598.63	7,983.95	8,270.24	1/4	1/4
1/2	4,933.16	5,526.73	6,101.19	6,647.05	7,153.51	7,607.45	7,991.06	8,274.77	1/2	1/2
3/4	4,945.66	5,538.92	6,112.89	6,658.04	7,163.56	7,616.23	7,998.13	8,279.25	3/4	3/4
2	4,958.16	5,551.11	6,124.57	6,669.02	7,173.58	7,624.98	8,005.16	8,283.64	2	2
1/4	4,970.65	5,563.29	6,136.24	6,679.98	7,183.58	7,633.70	8,012.14	8,287.96	1/4	1/4
1/2	4,983.14	5,575.46	6,147.90	6,690.92	7,193.56	7,642.40	8,019.09	8,292.20	1/2	1/2
3/4	4,995.62	5,587.61	6,159.55	6,701.84	7,203.51	7,651.06	8,025.98	8,296.37	3/4	3/4
3	5,008.10	5,599.77	6,171.19	6,712.75	7,213.44	7,659.68	8,032.83	8,300.45	3	3
1/4	5,020.57	5,611.91	6,182.81	6,723.64	7,223.34	7,668.28	8,039.65	8,304.46	1/4	1/4
1/2	5,033.04	5,624.04	6,194.42	6,734.52	7,233.22	7,676.85	8,046.41	8,308.39	1/2	1/2
3/4	5,045.50	5,636.17	6,206.02	6,745.37	7,243.08	7,685.39	8,053.13	8,312.22	3/4	3/4
4	5,057.96	5,648.28	6,217.60	6,756.20	7,252.91	7,693.88	8,059.81	8,315.98	4	4
1/4	5,070.41	5,660.39	6,229.17	6,767.02	7,262.73	7,702.36	8,066.43	8,319.64	1/4	1/4
1/2	5,082.86	5,672.49	6,240.73	6,777.82	7,272.51	7,710.80	8,073.01	8,323.21	1/2	1/2
3/4	5,095.30	5,684.58	6,252.27	6,788.60	7,282.27	7,719.20	8,079.55	8,326.70	3/4	3/4
5	5,107.77	5,696.65	6,263.80	6,799.36	7,292.01	7,727.58	8,086.04	8,330.08	5	5
1/4	5,120.13	5,708.73	6,275.31	6,810.14	7,301.73	7,735.92	8,092.48	8,333.37	1/4	1/4
1/2	5,132.59	5,720.79	6,286.82	6,820.83	7,311.41	7,744.22	8,098.87	8,336.56	1/2	1/2
3/4	5,145.01	5,732.84	6,298.31	6,831.54	7,321.08	7,752.50	8,105.22	8,339.64	3/4	3/4
6	5,157.42	5,744.88	6,309.78	6,842.23	7,330.71	7,760.74	8,111.51	8,342.62	6	6
1/4	5,169.83	5,756.91	6,321.24	6,852.90	7,340.33	7,768.94	8,117.76	8,345.47	1/4	1/4
1/2	5,182.22	5,768.93	6,332.68	6,863.54	7,349.91	7,777.12	8,123.95	8,348.22	1/2	1/2
3/4	5,194.63	5,780.94	6,344.14	6,874.18	7,359.48	7,785.25	8,130.10	8,350.84	3/4	3/4
7	5,207.01	5,792.95	6,355.54	6,884.79	7,369.01	7,793.35	8,136.20	8,353.33	7	7
1/4	5,219.40	5,804.94	6,366.94	6,895.39	7,378.53	7,801.42	8,142.24	8,355.68	1/4	1/4
1/2	5,231.77	5,816.92	6,378.33	6,905.95	7,388.00	7,809.46	8,148.23	8,357.90	1/2	1/2
3/4	5,244.15	5,828.88	6,389.70	6,916.51	7,397.46	7,817.46	8,154.17	8,359.96	3/4	3/4
8	5,256.51	5,840.85	6,401.06	6,927.04	7,406.89	7,825.41	8,160.06	8,361.84	8	8
1/4	5,268.86	5,852.80	6,412.41	6,937.55	7,416.30	7,833.35	8,165.89	8,363.56	1/4	1/4
1/2	5,281.22	5,864.74	6,423.73	6,948.05	7,425.68	7,841.23	8,171.67	8,365.06	1/2	1/2
3/4	5,293.56	5,876.66	6,435.05	6,958.52	7,435.03	7,849.09	8,177.39	8,366.33	3/4	3/4
9	5,305.93	5,888.59	6,446.35	6,968.97	7,444.36	7,856.91	8,183.06	8,367.32	9	9
1/4	5,318.23	5,900.49	6,457.63	6,979.40	7,453.66	7,864.68	8,188.67	8,368.67	1/4	1/4
1/2	5,330.55	5,912.39	6,468.90	6,989.82	7,462.93	7,872.43	8,194.23	8,369.94	1/2	1/2
3/4	5,342.87	5,924.25	6,480.15	6,999.20	7,472.17	7,880.14	8,199.72	8,371.22	3/4	3/4
10	5,355.18	5,936.17	6,491.39	7,010.57	7,481.40	7,887.80	8,205.16	8,372.51	10	10
1/4	5,367.49	5,948.02	6,502.62	7,020.93	7,490.58	7,895.44	8,210.55	8,373.80	1/4	1/4
1/2	5,379.78	5,959.87	6,513.82	7,031.25	7,499.74	7,903.03	8,215.87	8,375.09	1/2	1/2
3/4	5,392.07	5,971.71	6,525.01	7,041.56	7,508.88	7,910.59	8,221.13	8,376.38	3/4	3/4
11	5,404.35	5,983.54	6,536.19	7,051.85	7,517.98	7,918.10	8,226.33	8,377.67	11	11
1/4	5,416.62	5,995.35	6,547.35	7,062.12	7,527.06	7,925.58	8,231.47	8,378.96	1/4	1/4
1/2	5,428.88	6,007.16	6,558.49	7,072.36	7,536.11	7,933.02	8,236.55	8,380.25	1/2	1/2
3/4	5,441.14	6,018.95	6,569.62	7,082.58	7,545.13	7,940.41	8,241.56	8,381.54	3/4	3/4

NOTE: TABLE SCALED FROM EXTREME BOTTOM OF TANK. BARGE SHOULD BE ON EVEN KEEL WHEN GAUGING.

CAPACITIES REFLECT EXPANSION OF TANK SHELL. FOR AN OPERATING TEMPERATURE OF 80 F.

INNAUGE TABLE

STRAPPED: 3/17/09

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION

