



INSPECTORATE

ISO 9002 ACCREDITED

BARGE "TMS-451"
TEPPCO MARINE SERVICE.

TANK NO.
PORT

Capacities in Barrels

Page 1 of 2

Table with columns for depth (0 to 9 feet) and various capacity measurements. Each cell contains a numerical value and a fraction (e.g., 180.35 0/1).

NOTE: TABLE SCALED FROM EXTREME BOTTOM OF TANK.
BARGE SHOULD BE ON EVEN KEEL WHEN GAUGING.
CAPACITIES REFLECT EXPANSION OF TANK SHELL.
FOR AN OPERATING TEMPERATURE OF 60 F.

INNAGE TABLE

STRAPPED: 5/15/09
WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE
IN ACCORDANCE WITH APPLICABLE API STANDARDS AND
ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION



INSPECTORATE

ISO 9002 ACCREDITED

BARGE "TMS-451"
TEPCO MARINE SERVICE.

TANK NO.
PORT

Capacities in Barrels

Page 2 of 2

	10 FEET	11 FEET	12 FEET	13 FEET	14 FEET	15 FEET	16 FEET	17 FEET	18 FEET	19 FEET
0	4,903.07	5,507.46	6,095.15	6,657.02	7,182.86	7,660.57	8,074.42	8,400.55	8,580.90	0
1/4	4,915.77	5,519.90	6,107.15	6,668.37	7,193.95	7,669.91	8,082.21	8,406.14		1/4
1/2	4,928.47	5,532.34	6,119.14	6,679.11	7,193.82	7,679.22	8,089.97	8,411.67		1/2
3/4	4,941.17	5,544.77	6,131.12	6,691.04	7,214.27	7,688.49	8,097.69	8,417.15		3/4
1	4,953.86	5,557.20	6,143.08	6,702.36	7,224.69	7,697.75	8,105.37	8,422.57		1
1/4	4,966.55	5,569.61	6,155.04	6,713.66	7,235.10	7,706.97	8,113.02	8,427.92		1/4
1/2	4,979.24	5,582.01	6,166.99	6,724.94	7,245.49	7,716.18	8,120.63	8,433.22		1/2
3/4	4,991.92	5,594.41	6,178.92	6,736.20	7,255.85	7,725.34	8,128.19	8,438.45		3/4
2	5,004.59	5,606.81	6,190.84	6,747.45	7,266.19	7,734.48	8,135.71	8,443.62		2
1/4	5,017.26	5,619.19	6,202.75	6,758.69	7,276.51	7,743.60	8,143.21	8,448.73		1/4
1/2	5,029.94	5,631.57	6,214.65	6,769.90	7,286.80	7,752.68	8,150.65	8,453.78		1/2
3/4	5,042.60	5,643.93	6,226.54	6,781.10	7,297.08	7,761.73	8,158.06	8,458.76		3/4
3	5,055.26	5,656.29	6,238.41	6,792.28	7,307.33	7,770.75	8,165.43	8,463.67		3
1/4	5,067.91	5,668.65	6,250.27	6,803.45	7,317.57	7,779.75	8,172.75	8,468.52		1/4
1/2	5,080.57	5,680.98	6,262.12	6,814.60	7,327.77	7,788.72	8,180.04	8,473.30		1/2
3/4	5,093.21	5,693.32	6,273.95	6,825.73	7,337.96	7,797.65	8,187.28	8,478.01		3/4
4	5,105.85	5,705.64	6,285.78	6,836.84	7,348.12	7,806.55	8,194.48	8,482.65		4
1/4	5,118.49	5,717.96	6,297.59	6,847.94	7,358.27	7,815.43	8,201.64	8,487.21		1/4
1/2	5,131.13	5,730.27	6,309.39	6,859.03	7,368.38	7,824.27	8,208.75	8,491.71		1/2
3/4	5,143.75	5,742.57	6,321.17	6,870.08	7,378.48	7,833.08	8,215.83	8,496.13		3/4
5	5,156.37	5,754.86	6,332.95	6,881.13	7,388.55	7,841.87	8,222.86	8,500.48		5
1/4	5,168.99	5,767.17	6,344.71	6,892.16	7,398.59	7,850.62	8,229.85	8,504.75		1/4
1/2	5,181.60	5,779.42	6,356.46	6,903.17	7,408.62	7,859.34	8,236.79	8,508.94		1/2
3/4	5,194.21	5,791.68	6,368.19	6,914.14	7,418.62	7,868.02	8,243.69	8,513.06		3/4
6	5,206.81	5,803.95	6,379.91	6,925.17	7,428.60	7,876.69	8,250.55	8,517.09		6
1/4	5,219.41	5,816.19	6,391.62	6,936.09	7,438.56	7,885.31	8,257.36	8,521.04		1/4
1/2	5,232.52	5,828.43	6,403.32	6,947.03	7,448.48	7,893.90	8,264.11	8,524.91		1/2
3/4	5,244.59	5,840.65	6,415.00	6,957.95	7,458.39	7,902.46	8,270.84	8,528.68		3/4
7	5,257.16	5,852.87	6,426.68	6,968.85	7,468.27	7,910.99	8,277.51	8,532.37		7
1/4	5,269.74	5,865.08	6,438.31	6,979.74	7,478.13	7,919.49	8,284.13	8,535.97		1/4
1/2	5,282.31	5,877.28	6,449.96	6,990.60	7,487.96	7,927.95	8,290.71	8,539.47		1/2
3/4	5,294.87	5,889.48	6,461.58	7,001.45	7,497.76	7,936.38	8,297.24	8,542.88		3/4
8	5,307.42	5,901.66	6,473.20	7,012.28	7,507.55	7,944.78	8,303.73	8,546.20		8
1/4	5,319.97	5,913.83	6,484.79	7,023.09	7,517.30	7,953.15	8,310.16	8,549.40		1/4
1/2	5,332.52	5,925.98	6,496.37	7,033.88	7,527.04	7,961.47	8,316.55	8,552.50		1/2
3/4	5,345.06	5,938.13	6,507.94	7,044.64	7,536.75	7,969.77	8,322.88	8,555.50		3/4
9	5,357.59	5,950.28	6,519.50	7,055.39	7,546.43	7,978.03	8,329.17	8,558.38		9
1/4	5,370.12	5,962.41	6,531.04	7,066.13	7,556.08	7,986.26	8,335.41	8,561.14		1/4
1/2	5,382.63	5,974.53	6,542.57	7,076.83	7,565.72	7,994.45	8,341.60	8,563.77		1/2
3/4	5,395.15	5,986.65	6,554.08	7,087.53	7,575.32	8,002.61	8,347.73	8,566.28		3/4
10	5,407.65	5,998.74	6,565.57	7,098.20	7,584.90	8,010.73	8,353.81	8,568.66		10
1/4	5,420.16	6,010.82	6,577.06	7,108.85	7,594.45	8,018.82	8,359.85	8,570.88		1/4
1/2	5,432.64	6,022.90	6,588.53	7,119.49	7,603.97	8,026.87	8,365.82	8,572.96		1/2
3/4	5,445.13	6,034.97	6,599.98	7,130.10	7,613.47	8,034.89	8,371.75	8,574.86		3/4
11	5,457.62	6,047.03	6,611.42	7,140.69	7,622.95	8,042.87	8,377.62	8,576.58		11
1/4	5,470.09	6,059.07	6,622.84	7,151.26	7,632.39	8,050.81	8,383.43	8,578.10		1/4
1/2	5,482.55	6,071.11	6,634.24	7,161.82	7,641.81	8,058.71	8,389.20	8,579.37		1/2
3/4	5,495.01	6,083.14	6,645.64	7,172.35	7,651.20	8,066.59	8,394.90	8,580.36		3/4

NOTE: TABLE SCALED FROM EXTREME BOTTOM OF TANK.
BARGE SHOULD BE ON EVEN KEEL WHEN GAUGING.
CAPACITIES REFLECT EXPANSION OF TANK SHELL.
FOR AN OPERATING TEMPERATURE OF 60 F.

INNAGE TABLE

STRAPPED: 5/15/09
WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE
IN ACCORDANCE WITH APPLICABLE API STANDARDS AND
ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION



INSPECTORATE

ISO 9002 ACCREDITED

BARGE "TMS-451"
TEPCO MARINE SERVICE.

TANK NO.
STARBOARD

Capacities in Barrels

Page 2 of 2

Table with 19 columns (10 FEET to 19 FEET) and multiple rows of capacity data. Each cell contains a numerical value and a fraction (e.g., 0, 1/4, 1/2, 3/4).

NOTE: TABLE SCALED FROM EXTREME BOTTOM OF TANK.
BARGE SHOULD BE ON EVEN KEEL WHEN GAUGING.
CAPACITIES REFLECT EXPANSION OF TANK SHELL
FOR AN OPERATING TEMPERATURE OF 60 F.

INNAGE TABLE

STRAPPED: 5/15/09
WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE
IN ACCORDANCE WITH APPLICABLE API STANDARDS AND
ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.
INSPECTORATE AMERICA CORPORATION